pg 1 of 2

WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety

OFFICE USE ONLY
Log No. 35838
Permit No.
Basin 87

PRINT OR TYPE ONLY

NOTICE OF INTENT NO. 1726

1. OWNER NV Medical Liability Ins. Co./Al Ashley
MAILING ADDRESS P.O. Box 7456, Reno, NV 89510
ADDRESS AT WELL LOCATION Mobil Station, SE Corner of E 4th & Lake Streets, Reno, NV

2. LOCATION SE ¼ NE ¼ Sec. 11 T 19N N/S R 19 E Washoe County
PERMIT NO. M/O #367 (Issued by Water Resources) B-1 MW-1 (Parcel No.) Close to downtown area (Subdivision Name)

3. TYPE OF WORK
New Well [X] Recondition [ ]
Deepen [ ] Other [ ]

4. PROPOSED USE Monitoring X
Domestic [ ] Irrigation [ ] Test [ ]
Municipal [ ] Industrial [ ] Stock [ ]

5. TYPE WELL
Cable [ ] Rotary [X]
Other [ ] Air

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Asphalt, poorly graded brown sand		0	1	1
Light brown silty sand		1	2	1
Brown clayey sand		2	4	2
Light lean brown clay		4	9	5
Light brown silty sand		9	24	15
Gray brown poorly graded gravel		24	29.4	5.4

NOTE: THIS LOG TO REPLACE INCOMPLETE LOG 3-19-91

Final information supplied from Harding Lawson 4-23-91

Date started 2-13-91, 19
Date completed 2-13-91, 19

7. WELL TEST DATA

Pump RPM	G.P.M.	Draw Down	After Hours Pump

BAILER TEST
G.P.M. ..... Draw down ..... feet ..... hours
G.P.M. ..... Draw down ..... feet ..... hours
G.P.M. ..... Draw down ..... feet ..... hours

8. WELL CONSTRUCTION
Diameter 9 5/16 inches Total depth 29.4 feet
..... inches
..... inches
Casing record 29 ft. PVC installed.
Weight per foot ..... Thickness sch 40

Diameter	From	To
2" inches	0 feet	29 feet
inches	feet	feet
inches	feet	feet
inches	feet	feet
inches	feet	feet
inches	feet	feet

Surface seal: Yes [X] No [ ] Type Bentonite 2 ft & Cement grout
Depth of seal 16 ft. feet
Gravel packed: Yes [X] No [ ] Sand #3 Monteray
Gravel packed from 18 feet to 29.4 feet

Perforations:
Type perforation factory sawed slot
Size perforation 0.01"
From 19 feet to 29 feet
From ..... feet to ..... feet
From ..... feet to ..... feet
From ..... feet to ..... feet
From ..... feet to ..... feet

9. WATER LEVEL
Static water level 24.1 2-15-90 feet below land surface
Flow N/A G.P.M. P.S.I.
Water temperature ..... °F Quality .....

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Wayne Drilling, Inc. (Contractor)
Address P.O. Box 12370, Reno, NV 89510 (Contractor)
Nevada contractor's license number issued by the State Contractor's Board 22549
Nevada contractor's driller's number issued by the Division of Water Resources 908
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 908
Signed [signature] (By driller performing actual drilling on site or contractor)
Date April 29, 1991

(Rev. 11-85) USE ADDITIONAL SHEETS IF NECESSARY (O)-627

pg 2 of 2

Log No. 35838

LOG OF BORING B-1

Equipment Tubex Pneumatic Drill Rig

Elevation _____ Date 2/13/91

Depth (ft) | Sample

0 — ASPHALT CONCRETE

BROWN POORLY GRADED SAND WITH SILT AND GRAVEL (SP-SM); dense, moist, base — FILL

LIGHT BROWN SILTY SAND (SM); dense, moist-wet

5 — BROWN CLAYEY SAND (SC); medium dense, wet, occasional gravel dia. 5-3/4"

LIGHT BROWN LEAN CLAY (CL); medium stiff to stiff, wet

10 — LIGHT BROWN SILTY SAND (SM); medium dense, moist, wet lenses of sandy silt

15

20 — Color change to gray brown, medium dense to dense, with lenses of poorly graded sand with silt

25 — GRAY BROWN POORLY GRADED GRAVEL WITH SILT AND SAND (GP-GM); dense to very dense, with cobbles

30 — Boring terminated at 29.4'. Free groundwater measured at 24.1' on 2-15-91. Converted to monitoring well MW-1 on 2-13-91.

35

40