

PRINT OR TYPE ONLY
 DO NOT WRITE ON BACK

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
 Log No. 37148
 Permit No.
 Basin Q04-WARM SPRINGS V.
 NOTICE OF INTENT NO. 17981

1. OWNER STEVE & GLORIA REITER ADDRESS AT WELL LOCATION
 MAILING ADDRESS 441 St. Francis Blvd. 14855 (Pyramid Hwy.) S.R. 445
 Daly City, CA. 94015 Reno, NV 89510
 2. LOCATION NE SE 1/4 SW 1/4 Sec. 24 T. 22N N/S R. 20 E Washoe County
 PERMIT NO. 076-272-03 Parcel No. Palomino Valley Unit 5 24-2-0-5
 Issued by Water Resources Subdivision Name

3. WORK PERFORMED
 New Well Replace Recondition
 Deepen Abandon Other
 4. PROPOSED USE
 Domestic Irrigation Test
 Municipal/Industrial Monitor Stock
 5. WELL TYPE
 Cable Rotary RVC
 Air Other

6. LITHOLOGIC LOG

| Material | Water Strata | From | To | Thick-ness |
|----------------------------------|--------------|------|-----|------------|
| Top soil with boulders & gravels | | 0 | 5 | 5 |
| Brown sandy clay & gravels | | 5 | 38 | 33 |
| Brown sandy clay | | 38 | 80 | 42 |
| Rusty brown clay | | 80 | 112 | 32 |
| White volcanic rock | | 112 | 132 | 21 |
| Soft zone | X | 132 | 135 | 3 |
| White volcanic rock | | 135 | 145 | 10 |
| Brown volcanic rock | | 145 | 155 | 10 |
| Soft zone | X | 155 | 160 | 5 |
| Brown volcanic rock | | 160 | 178 | 18 |
| Soft zone | X | 178 | 180 | 2 |
| Brown volcanic rock | | 180 | 191 | 11 |
| Soft zone | X | 191 | 192 | 1 |
| Brown volcanic rock | | 192 | 200 | 8 |

8. WELL CONSTRUCTION
 Depth Drilled 200 Feet Depth Cased 200 Feet
 HOLE DIAMETER (BIT SIZE)
 From To
 10 Inches 0 Feet 50 Feet
 8 5/8 Inches 50 Feet 200 Feet
 Inches Feet Feet

CASING SCHEDULE

| Size O.D. (Inches) | Weight/Ft. (Pounds) | Wall Thickness (Inches) | From (Feet) | To (Feet) |
|--------------------|---------------------|-------------------------|-------------|-----------|
| 6 5/8 | 12.92 | .188 | 0 | 200 |

Perforations:
 Type perforation factory sawed slot
 Size perforation 3/32 x 3 x 5 around
 From 132 feet to 152 feet
 From 172 feet to 192 feet
 From feet to feet
 From feet to feet

Surface Seal: Yes No Seal Type:
 Depth of Seal 50 ft Neat Cement
 Placement Method: Pumped Cement Grout
 Poured Concrete Grout
 Gravel Packed: Yes No
 From 50 feet to 200 feet

9. WATER LEVEL
 Static water level 84 feet below land surface
 Artesian flow 50+ G.P.M. P.S.I.
 Water temperature cold °F Quality clear

10. DRILLER'S CERTIFICATION
 This well was drilled under my supervision and the report is true to the best of my knowledge.
 Name Wayne Drilling, Inc. Contractor
 Address P.O. Box 12370 Reno, NV 89510 Contractor
 Nevada contractor's license number issued by the State Contractor's Board 22549
 Nevada driller's license number issued by the Division of Water Resources, the on-site driller 923
 Signed [Signature] By driller performing actual drilling on site or contractor
 Date August 23, 1991

Date started 8-20-91
 Date completed 8-19-91

7. WELL TEST DATA

| TEST METHOD: | G.P.M. | Draw Down (Feet Below Static) | Time (Hours) |
|---|--------|-------------------------------|--------------|
| <input type="checkbox"/> Bailer <input type="checkbox"/> Pump <input type="checkbox"/> Air Lift | | | |