WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 37390
Permit No.
Basin 129

NOTICE OF INTENT NO. 1915

1. OWNER COEUR ROCHESTER INC.
MAILING ADDRESS P.O. Box 1057
Lovelock, NV 89419

ADDRESS AT WELL LOCATION Coeur Rochester Mine

2. LOCATION SE¼ NW ¼ SE ¼ Sec. 22 T. 28 N/S R. 34 E. Pershing County
~~PERMIT~~ NO. Waiver M/O 409
Issued by Water Resources | Parcel No. | Subdivision Name

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Alluvium		0	30	30
~~Dry hole~~				

Installed cap on bottom of five feet 2 inch Schedule 40 .010 inch slotted pvc casing & installed in hole with 25 feet of blank two inch schedule 40 pvc casing on top with about 8" stickup placed 2-100 pound bags of 8 mesh sand around and over top of slots. Installed 12' of 6" o.d. steel casing with locking cap in top of hole and back filled around both casings from 0'-24' with bentonite pellets.

Used 15-50# bags of bentonite pellets

'91 JUL 16 A10:24
STATE ENGINEER'S OFFICE

Date started July 9, 1991
Date completed July 9, 1991

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
N/A			

8. WELL CONSTRUCTION
Depth Drilled 30 Feet Depth Cased 30 Feet

HOLE DIAMETER (BIT SIZE)

	From	To
~~10 Inches~~	~~0 Feet~~	~~10 Feet~~
5½ Inches	10 Feet	30 Feet
Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2-3/8	PVC	Schedule 40	+.75	30

Perforations:
Type perforation slots
Size perforation .010 inch
From 25 feet to 30 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 24 feet
Placement Method: ☐ Pumped ☒ Poured
~~Gravel~~ SAND Packed: ☒ Yes ☐ No
From 24 feet to 30 feet

Seal Type:
☐ Neat Cement
☐ Cement Grout
☐ Concrete Grout
X Bentonite pellets

9. WATER LEVEL
Static water level DRY HOLE feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name HACKWORTH DRILLING, INC. Contractor
Address P.O. Box 850 Contractor
Elko, NV 89801
Nevada contractor's license number issued by the State Contractor's Board 020582
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1166
Signed [signature] By driller performing actual drilling on site or contractor
Date 7-15-91

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627