WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 38302
Permit No.
Basin 105

NOTICE OF INTENT NO. 19746

1. OWNER Ralph Parish
MAILING ADDRESS P.O. Box 1412 Minden NV 89410
ADDRESS AT WELL LOCATION 1531 Salt Bush Ct. Gardnerville NV

2. LOCATION NW ¼ SW ¼ Sec. 36 T 13 N/S R 20 E Douglas County
PERMIT NO. (Issued by Water Resources) 23472-27 (Parcel No.) Wildflower (Subdivision Name)

3. WORK PERFORMED
☑ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☑ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☑ Rotary ☐ RVC
☐ Air ☐ Other Mud

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Overburden w/Cobbles		0	45	45
Brown Sandy Clay		45	55	10
Soft Sandstone w/Small Clay Seams		55	110	55
3/8 Gravels		110	115	5
3/8 Gravels w/ Small Clay Seams		115	160	45
Firm Sandstone		160	210	50
Small Cobbles		210	290	80
Gravels w/Small Amount of Water	XX	290	315	25
Brown Clay		315	345	30
Gray Clay		345	410	65
Small Gravels		410	415	5
Water Zone	XXX			
Gray Clay		415	420	5
Gravels Water Zone	XXX	420	430	10

Date started 7-28, 19 97
Date completed 7-30, 19 97

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☑ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
30	25	2 Hr.

8. WELL CONSTRUCTION
Depth Drilled 430 Feet Depth Cased 430 Feet

HOLE DIAMETER (BIT SIZE)

Inches	From (Feet)	To (Feet)
11 3/4	0	55
10	55	420

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8	13.83	.188	0	430

Perforations:
Type perforation Mill Slot
Size perforation 3/32 x 3 1/2
From ... feet to ... feet
From ... feet to ... feet
From ... feet to ... feet
From ... feet to ... feet
From ... feet to ... feet

Surface Seal: ☑ Yes ☐ No
Depth of Seal 55
Placement Method: ☐ Pumped ☑ Poured
Seal Type: ☐ Neat Cement ☑ Cement Grout ☐ Concrete Grout

Gravel Packed: ☐ Yes ☐ No
From 55 feet to 420 feet

9. WATER LEVEL
Static water level 220 feet below land surface
Artesian flow ... G.P.M. 30 P.S.I.
Water temperature Cold °F Quality Good

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name A & H PUMP CO. 5551 Hwy. 50 East #3 Carson City, Nevada 89701 Contractor
Address 883-0459 - 883-4[illegible] 885-1896 Contractor

Nevada contractor's license number issued by the State Contractor's Board 31839
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1674
Signed Joe Butts
By driller performing actual drilling on site or contractor
Date

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627