

OFFICE USE ONLY  
 Log No. 38348  
 Permit No. \_\_\_\_\_  
 Basin. 7-928

PRINT OR TYPE ONLY  
 DO NOT WRITE ON BACK

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 20116

1. OWNER LESLIE ESTES ADDRESS AT WELL LOCATION \_\_\_\_\_  
 MAILING ADDRESS 7730 Tamra Drive \_\_\_\_\_  
Reno, NV 89506 \_\_\_\_\_  
 2. LOCATION SE 1/4 SE 1/4 Sec 3 T 21N N/S R 19 E \_\_\_\_\_  
Washeo County \_\_\_\_\_  
 PERMIT NO 88-081-22 \_\_\_\_\_  
 Issued by Water Resources Parcel No. \_\_\_\_\_  
Golden Valley \_\_\_\_\_  
 Subdivision Name

3. WORK PERFORMED  
 New Well  Replace  Recondition  
 Deepen  Abandon  Other \_\_\_\_\_  
 4. PROPOSED USE  
 Domestic  Irrigation  Test  
 Municipal/Industrial  Monitor  Stock  
 5. WELL TYPE  
 Cable  Rotary  RVC  
 Air  Other \_\_\_\_\_

6. LITHOLOGIC LOG

| Material        | Water Strata | From | To  | Thick-ness |
|-----------------|--------------|------|-----|------------|
| WELL DEEPENING: |              |      |     |            |
| Fill            |              | 234  | 241 | 7          |
| Gray granite    |              | 241  | 255 | 14         |
| Fracture        | X            | 255  | 257 | 2          |
| Gray granite    |              | 257  | 290 | 33         |
| Fracture        | X            | 290  | 292 | 2          |
| Gray granite    |              | 292  | 317 | 25         |
| Fracture        | X            | 317  | 320 | 3          |
| Gray granite    |              | 320  | 325 | 5          |

8. WELL CONSTRUCTION  
 Depth Drilled 325 Feet Depth Cased 325 Feet  
 HOLE DIAMETER (BIT SIZE)  
 From 6 1/8 Inches 234 Feet To 325 Feet  
 \_\_\_\_\_ Inches \_\_\_\_\_ Feet \_\_\_\_\_ Feet  
 \_\_\_\_\_ Inches \_\_\_\_\_ Feet \_\_\_\_\_ Feet

CASING SCHEDULE

| Size O.D. (Inches) | Weight/Ft. (Pounds) | Wall Thickness (Inches) | From (Feet) | To (Feet) |
|--------------------|---------------------|-------------------------|-------------|-----------|
| 5"                 |                     | .188                    | 0           | 325       |

Perforations:  
 Type perforation factory sawed slot  
 Size perforation 3/32 x 3 x 5 around  
 From 265 feet to 325 feet  
 From \_\_\_\_\_ feet to \_\_\_\_\_ feet

Surface Seal:  Yes  No Seal Type:  
 Neat Cement  
 Cement Grout  
 Concrete Grout  
 Depth of Seal \_\_\_\_\_  
 Placement Method:  Pumped  Poured  
 Gravel Packed:  Yes  No  
 From 240 feet to 325 feet

9. WATER LEVEL  
 Static water level 225 feet below land surface  
 Artesian flow 20 G.P.M. \_\_\_\_\_ P.S.I.  
 Water temperature cold °F Quality clear

10. DRILLER'S CERTIFICATION  
 This well was drilled under my supervision and the report is true to the best of my knowledge.  
 Name Wayne Drilling, Inc. Contractor  
 Address P.O. Box 12370 Contractor  
Reno, NV 89510  
 Nevada contractor's license number issued by the State Contractor's Board 22549  
 Nevada driller's license number issued by the Division of Water Resources, the on-site driller 923  
 Signed [Signature]  
 By driller performing actual drilling on site or contractor  
 Date July 17, 1992

Date started 7-14-92, 19\_\_\_\_\_  
 Date completed 7-15-92, 19\_\_\_\_\_

7. WELL TEST DATA

TEST METHOD:  Bailer  Pump  Air Lift

| G.P.M. | Draw Down (Feet Below Static) | Time (Hours) |
|--------|-------------------------------|--------------|
|        |                               |              |
|        |                               |              |
|        |                               |              |
|        |                               |              |