

Copy in File

WHITE-DIVISION OF WATER RESOURCES
CANARY-CLIENT'S COPY
PINK-WELL DRILLER'S COPY

STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 38785
Permit No. 57032-T
Basin. 4-69-PARADISE V.

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 20061

1. OWNER Harold Boggio
MAILING ADDRESS P.O. Box 36
Paradise Valley, Nevada 89426
ADDRESS AT WELL LOCATION 1/4 mi. South of
Paradise- 100 yds. West off Hwy 8-B
Paradise Valley, Nevada
2. LOCATION SW 1/4 SW 1/4 Sec. 25 T 42 N 39 E Humboldt County
PERMIT NO. 57032-T Issued by Water Resources Parcel No. Subdivision Name

3. WORK PERFORMED
 New Well Replace Recondition
 Deepen Abandon Other
4. PROPOSED USE
 Domestic Irrigation Test
 Municipal/Industrial Monitor Stock
5. WELL TYPE
 Cable Rotary RVC
 Air Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Top Soil		0	2	2
Sand		2	6	4
Sand & Gravel		6	10	4
Sand & Clay		10	19	9
Cobbles w/s Clay		19	37	18
Clay / Gravel		37	41	4
Sand and Gravel		41	49	8
Sandy Clay		49	67	18
Clay / Sand Stringers		67	168	101
Sand		168	175	7
Clay / Sand Stringers		175	190	15
Sand and Gravel		190	195	5
Clay / Sand Stringers		195	202	7
Sand		202	210	8
Clay / Sand Stringers		210	258	48
Sand		258	264	6
Clay / Sand Stringers		264	310	46
Sand		310	319	9
Clay / Sand Stringers		319	486	167
Sand and Gravel		486	495	9
Clay / Sand Stringers		495	640	145
Clay		640	660	20
Sand and Gravel		660	667	7
Clay		667	700	33

8. WELL CONSTRUCTION
Depth Drilled 700 Feet Depth Cased 680 Feet
HOLE DIAMETER (BIT SIZE)
From To
36 Inches 0 Feet 50 Feet
25 Inches 50 Feet 700 Feet
Inches Feet Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
30		conductor	0	50
12 3/4	33.38	.250	0	50

Perforations:
Type perforation Mill
Size perforation 1/8 / 2
From (see attached) feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: Yes No Seal Type:
Depth of Seal 50 Neat Cement
Placement Method: Pumped Cement Grout
 Poured Concrete Grout
Gravel Packed: Yes No
From 0 feet to 680 feet

9. WATER LEVEL
Static water level 18 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature cold °F Quality good

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Humboldt Drilling and Pump Co. Contractor
Address P.O. Box 590 Contractor
Winnemucca, Nevada 89446-0590
Nevada contractor's license number issued by the State Contractor's Board 015234
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1536/1448
Signed Don Sanchez Jr By driller performing actual drilling on site or contractor
Date 8-21-92

Date started 8/10 1992
Date completed 8/18 1992

7. WELL TEST DATA

TEST METHOD:	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
<input type="checkbox"/> Bailer <input type="checkbox"/> Pump <input type="checkbox"/> Air Lift			
			did not test pump