WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 388226
Permit No.
Basin 08'73

NOTICE OF INTENT NO. 19700

1. OWNER Resna
MAILING ADDRESS 3164 Gold Camp Drive, Ste 200
Rancho Cordova, CA 95670

ADDRESS AT WELL LOCATION Unocal Corp.
1550 Pyramid Way
Sparks, Nevada

2. LOCATION NW ¼ NW ¼ Sec. 4 T. 19N N/S R. 20 E. Washoe County
PERMIT NO. M/O-314-A MW-1 (Issued by Water Resources) Parcel No. Sparks Greenbrae&Pyradid Way (Subdivision Name)

3. WORK PERFORMED
[X] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Abandon [ ] Other

4. PROPOSED USE
[ ] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [X] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [X] Rotary [ ] RVC
[X] Air [X] Other Tubex 190

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Sand, some pea gravel (fill)		0	10	10
Cobbles, gravel and silt, pale yellowish brown		10	13.5	3.5
Silty, sand, some bravel, pale yellowish brown		13.5	17.5	4
Cobbles, sand and silt dark yellowish brown		17.5	34	16.5

Date started 3/23/92, 19
Date completed 3/23/92, 19

7. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [ ] Air Lift

	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
NO TEST			

8. WELL CONSTRUCTION
Depth Drilled 34 Feet Depth Cased 31.2 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
8 5/8 Inches		0 Feet	34 Feet
Inches		Feet	Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2" PVC		SCH 40	0	34
2" PVC end cap				
2" PVC locking cap				

Perforations:
Type perforation factory sawed slot
Size perforation .020 x 1¼ x 3 rows
From 16.5 feet to 31.2 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: [X] Yes [ ] No
Depth of Seal 2' bentonite
Placement Method: [ ] Pumped [X] Poured
Seal Type: 13' [X] Neat Cement [ ] Cement Grout [ ] Concrete Grout

Gravel Packed: [X] Yes [ ] No w/#2/16 sand
From 16 feet to 34 feet

9. WATER LEVEL
Static water level 18.1 feet below land surface
Artesian flow not known G.P.M. P.S.I.
Water temperature n/k °F Quality not known

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Wayne Drilling, Inc. (Contractor)
Address P.O. Box 21370 (Contractor)
Reno, NV 89510
Nevada contractor's license number issued by the State Contractor's Board 22549
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 908
Signed Gary C. Hedman (By driller performing actual drilling on site or contractor)
Date May 6, 1992

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627