WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY
PZ-92-7

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 39089
Permit No.
Basin 61

NOTICE OF INTENT NO. 19375

1. OWNER BARRICK GOLDSTRIKE
MAILING ADDRESS P.O. BOX 29
ELKO, NV 89803

ADDRESS AT WELL LOCATION
BARRICK GOLDSTRIKE MINE SITE

2. LOCATION SE ¼ SE ¼ Sec. 24 T 36 N/S X R 49 E EUREKA County
PERMIT NO. M/0441 (Issued by Water Resources) N/A (Parcel No.) N/A (Subdivision Name)

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☒ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
WEATHERED LIMESTONE		0	125	128
GRAY-BLACK LIMESTONE		125	215	90
CLAY		215	230	15
WEATHERED LIMESTONE		230	250	20
BLACK LIMESTONE		250	490	240
CLAY SEAMS		490	550	60
LIMESTONE GRAY-BLACK		550	1000	450

'92 APR 21 A10:08
STATE ENGINEER'S OFFICE

Date started APRIL 8, 19 92
Date completed APRIL 11, 19 92

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 1000 Feet Depth Cased 940 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
12¼	Inches	0	Feet	6	Feet
6½	Inches	6	Feet	1000	Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6.00	19	.280	0	6
1.25	2.25	.140	0	940
1.25	2.25	.140	0	600

Perforations:
Type perforation DRILLED
Size perforation 1/8"
From 1. 880 feet to 940 feet
From 2. 500 feet to 600 feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 50'
Placement Method: ☒ Pumped ☐ Poured
Seal Type: ☒ Neat Cement ☐ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 1. 860-1000 feet to 2. 50-600 feet

9. WATER LEVEL
Static water level 754 feet below land surface
Artesian flow 15 G.P.M. P.S.I.
Water temperature 70 °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name LANG EXPLORATORY DRILLING (Contractor)
Address 2286 WEST 1500 SOUTH (Contractor)
SALT LAKE CITY, UTAH 84104

Nevada contractor's license number issued by the State Contractor's Board 0021976

Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1410

Signed [signature] (By driller performing actual drilling on site or contractor)
Date APRIL 15, 1992

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627