WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 39203
Permit No.
Basin 85

NOTICE OF INTENT NO. 19664

1. OWNER: Clark Monson
MAILING ADDRESS: 3590 Erin Dr, Sparks, Nv 89436
ADDRESS AT WELL LOCATION: Calle de la Plata (Kratzo Ct) Parcel D

2. LOCATION: SE ¼ NW ¼ Sec. 19 T. 21 N/S R. 21 E. Washoe County
PERMIT NO. (Issued by Water Resources) 76-~~371-34~~ 372-08 (Parcel No.) Spanish Springs (Subdivision Name)

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☒ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☒ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Overburden		0	1	1
D.G. tan & brown		1	15	14
D.G. white		15	30	15
D.G. tan brown		30	33	3
D. G. white		33	100	67
D.G. white & tan		100	170	70
D.G. mostly tan some white		170	180	10
D.G. white tan & bluish white		180	215	35
Not as decomposed but still D.G. white black specs & tan		215	310	95
Granite medium hard	X	310	578	268
Bottom 25 ft hole is filled with bore hole cuttings.				

Date started 5/19/92, 19
Date completed 5/27/92, 19

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☒ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
20+		3

8. WELL CONSTRUCTION
Depth Drilled 578 Feet Depth Cased 553 Feet

HOLE DIAMETER (BIT SIZE)

Inches	From (Feet)	To (Feet)
10 5/8	0	50
8 ½	50	578

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8	12.92	.188	+1	553

Perforations:
Type perforation: factory
Size perforation: 3/32 X 3
From 363 feet to 383 feet
From 513 feet to 533 feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 50
Placement Method: ☐ Pumped ☒ Poured
Seal Type: ☐ Neat Cement ☐ Cement Grout ☒ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 50 feet to 553 feet

9. WATER LEVEL
Static water level 248 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name (Contractor): Aqua Drilling & Well Service, Inc
Address (Contractor): 625 Spice Islands Dr Suite L
Sparks, Nv 89431
Nevada contractor's license number issued by the State Contractor's Board: 15291
Nevada driller's license number issued by the Division of Water Resources, the on-site driller: 1804
Signed: Roger M. Thrall (By driller performing actual drilling on site or contractor)
Date: Roger M. Thrall 5/27/92

(Rev. 3 91)
USE ADDITIONAL SHEETS IF NECESSARY
(O)-627