WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 39234
Permit No.
Basin 102

NOTICE OF INTENT NO. 19357

1. OWNER Clarence Dugan
MAILING ADDRESS P.O. Box 1002 Penn Valley Calif 95946
ADDRESS AT WELL LOCATION 1048 4TH Silver Springs Nev 89429

2. LOCATION SW ¼ SW ¼ Sec. 7 T. 17 N/S R. 25 E. Lyon County
PERMIT NO. (Issued by Water Resources) 017-148-04 (Parcel No.) Butte #1 (Subdivision Name) LOT 49

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition ☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☒ Domestic ☐ Irrigation ☐ Test ☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC ☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Hard Pan		0	3	3
Fine Sand		3	10	7
Brown Clay		10	13	3
Brown Clay & Sand		13	16	3
Fine Sand		16	38	22
Brown Clay		38	48	10
Brown Clay & Sand		48	61	13
Grayish Clay & Sand		61	75	14
Grayish Clay & Gravel		75	77	2
Grayish Clay & Sand		77	88	11
Brown Clay & Sand		88	94	6
Coarse Sand & Gravel		94	114	20
Brown Clay		114	122	8
Coarse Sand/Gravel, Black Rock & Clay		122	134	12
Coarse Sand & Gravel		134	141	7
Coarse Sand with Small Clay Stratas	X	141	164	23

Date started 5-4, 1992
Date completed 5-5, 1992

7. WELL TEST DATA

TEST METHOD: ☒ Bailer ☐ Pump ☐ Air Lift

	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
Bailed	22	9	1/2

8. WELL CONSTRUCTION
Depth Drilled 163 Feet Depth Cased 164 Feet

HOLE DIAMETER (BIT SIZE)

Inches	From Feet	To Feet
10 3/8	0	163

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8	12.92	.188	+1	163

Perforations:
Type perforation Sawed
Size perforation 18 x 3 6 Rows
From feet to feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 50
Placement Method: ☒ Pumped ☐ Poured
Seal Type: ☐ Neat Cement ☒ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 50 feet to 163 feet

9. WATER LEVEL
Static water level 46 feet below land surface
Artesian flow — G.P.M. — P.S.I.
Water temperature Cold °F Quality Good

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name (Contractor) Osden Bros Drilling
Address (Contractor) 162 N Bybee Lane Yerington Nev 89447
Nevada contractor's license number issued by the State Contractor's Board 15646
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 634
Signed (By driller performing actual drilling on site or contractor) Larry Osden
Date 5-21-92

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627