WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

# WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 39307
Permit No.
Basin 92A

NOTICE OF INTENT NO. 21508

1. OWNER: JOHN JARDINE Sr.
MAILING ADDRESS: P.O. Box 5454, Reno, NV 89513
ADDRESS AT WELL LOCATION: 11090 Wagon Ho, Reno, NV 89506

2. LOCATION: NW ¼ SE ¼ Sec 25 T 21N N/S R 18 E Washoe County
PERMIT NO. (Issued by Water Resources) | Parcel No. 086-350-11 | Subdivision Name: Silver Knolls

3. WORK PERFORMED
[X] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Abandon [ ] Other

4. PROPOSED USE
[X] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [ ] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [X] Rotary [ ] RVC
[X] Air [ ] Other

6. LITHOLOGIC LOG

| Material | Water Strata | From | To | Thickness |
|---|---|---|---|---|
| Top soil | | 0 | 1 | 1 |
| Brown clay | | 1 | 48 | 47 |
| Soft zone (BROWN SAND) | | 48 | 51 | 3 |
| Brown clay | | 51 | 66 | 15 |
| Soft zone (GRANITE SANDS) | | 66 | 71 | 5 |
| Soft sandy brown clay | | 71 | 98 | 27 |
| Soft zone (FINE SAND) | X | 98 | 110 | 12 |
| Brown clay | | 110 | 118 | 8 |
| Soft zone (COARSE SAND) | X | 118 | 131 | 13 |
| Brown clay | | 131 | 133 | 2 |
| Soft zone (COARSE SANDS) | X | 133 | 142 | 9 |
| Brown sandy soft clay | | 142 | 147 | 5 |

Date started 6-19-92, 19
Date completed 6-19-92, 19

7. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [ ] Air Lift

| G.P.M. | Draw Down (Feet Below Static) | Time (Hours) |
|---|---|---|
| | | |

8. WELL CONSTRUCTION
Depth Drilled 147 Feet Depth Cased 147 Feet

HOLE DIAMETER (BIT SIZE)

| | | From | To |
|---|---|---|---|
| 10 Inches | | 0 Feet | 50 Feet |
| Inches | | Feet | Feet |
| Inches | | Feet | Feet |

CASING SCHEDULE

| Size O.D. (Inches) | Weight/Ft. (Pounds) | Wall Thickness (Inches) | From (Feet) | To (Feet) |
|---|---|---|---|---|
| 6 5/8 | | .188 | 0 | 147 |
| | | | | |
| | | | | |

Perforations:
Type perforation: factory sawed slot
Size perforation: 3/32 x 3 x 5 around
From 120 feet to 140 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: [X] Yes [ ] No
Depth of Seal 50
Placement Method: [ ] Pumped [X] Poured
Seal Type: [ ] Neat Cement [X] Cement Grout [ ] Concrete Grout

Gravel Packed: [X] Yes [ ] No
From 50 feet to 147 feet

9. WATER LEVEL
Static water level 47 feet below land surface
Artesian flow 20 G.P.M. P.S.I.
Water temperature cold °F Quality clear

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Wayne Drilling, Inc. (Contractor)
Address P.O. Box 12370, Reno, NV 89510 (Contractor)
Nevada contractor's license number issued by the State Contractor's Board 22549
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 923
Signed (By driller performing actual drilling on site or contractor)
Date June 22, 1992

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627