WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 39567
Permit No.
Basin 69 - PARADISE V.

NOTICE OF INTENT NO. 19946

1. OWNER Dewight Twomey
MAILING ADDRESS 98 Park Ridge #501
San Francisco, California 94131

ADDRESS AT WELL LOCATION Dutch Flat
#1 Opus Lane
Winnemucca, Nevada 89445

2. LOCATION S½ /N½ ¼ SE ¼ Sec. 19 T. 38 X N/S R. 39 E. Humboldt County

PERMIT NO. - (Issued by Water Resources) #5 (Parcel No.) - (Subdivision Name)

3. WORK PERFORMED
[X] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Abandon [ ] Other

4. PROPOSED USE
[X] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [ ] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [X] Rotary [ ] RVC
[ ] Air [ ] Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Sandy Clay		0	8	8
Sand		8	26	18
Sand w/s Cobbles		26	66	40
Clay w/s Sand		66	89	23
Sand		89	145	56
Sand w/s Clay Stringers		145	150	5

'92 SEP 25 P2:29
STATE ENGINEER

Date started 9-21, 1992
Date completed 9-22, 1992

7. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [X] Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
30	air on rig	

8. WELL CONSTRUCTION
Depth Drilled 150 Feet Depth Cased 150 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
10 Inches		0 Feet	150 Feet
Inches		Feet	Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6	12.92	.188	+2	110

Perforations:
Type perforation Mill Slot
Size perforation 1/8 X 3
From 110 feet to 150 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: [X] Yes [ ] No
Depth of Seal 50
Placement Method: [X] Pumped [ ] Poured

Seal Type:
[ ] Neat Cement
[ ] Cement Grout
[X] Concrete Grout

Gravel Packed: [X] Yes [ ] No
From 50 feet to 150 feet

9. WATER LEVEL
Static water level 45 feet below land surface
Artesian flow - G.P.M. - P.S.I.
Water temperature cold °F Quality good

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Humboldt Drilling and Pump Co. (Contractor)
Address P.O.Box 590 (Contractor)
Winnemucca, Nevada 89446-0590

Nevada contractor's license number issued by the State Contractor's Board 015234

Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1536

Signed [signature] (By driller performing actual drilling on site or contractor)
Date 9-25-92

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627