

PRINT OR TYPE ONLY  
 DO NOT WRITE ON BACK

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT No. 10839

1. OWNER SEA Consulting Eng. Inc. ADDRESS AT WELL LOCATION Downtown Reno  
 MAILING ADDRESS 950 Industrial Way Plaza & Center, Commercial/Lake  
Sparks, NV 89431-6092 Reno, NV  
 2. LOCATION SE 1/4 NE 1/4 Sec. 11 T. 19 N/S R. 19 E Washoe County  
 PERMIT NO. M/O 483 NW well Downtown Reno  
Issued by Water Resources Parcel No. Subdivision Name

3. WORK PERFORMED  
 New Well  Replace  Recondition  
 Deepen  Abandon  Other.....  
 4. PROPOSED USE  
 Domestic  Irrigation  Test  
 Municipal/Industrial  Monitor  Stock  
 5. WELL TYPE  
 Cable  Rotary  RVC  
 Air  Other Tubex 190

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Asphalt concrete		0	5"	5"
Base		5"	10"	5"
Moist, stiff, brown sandy clay with est. 80% med. plastic fines				
20% fine to coarse sand		10"	9'	9'2"
Brown silty sand with est. 20% non-plastic fines, 80% very fine fine sand		9.5	16'	6.5'
Dark gray cobbly sandy gravel with est. 30% fine-coarse sand, 70% gravel, predominately andesite/basalt and minor granitics		16	20	4
Brown slightly clayey cobbly gravelly sand with est. 10% low plastic fines, 50% sand, 40% gravel		20	30	10
Dark gray sandy gravel with est. 20% sand 80% subrounded andesitic gravel		30	34	4

8. WELL CONSTRUCTION  
 Depth Drilled 34 Feet Depth Cased 34 Feet  
 HOLE DIAMETER (BIT SIZE)  
 From 0 To 34  
9 5/16 Inches 0 Feet 34 Feet  
 \_\_\_\_\_ Inches \_\_\_\_\_ Feet \_\_\_\_\_ Feet  
 \_\_\_\_\_ Inches \_\_\_\_\_ Feet \_\_\_\_\_ Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
4" PVC		SCH	0	34
4" PVC	End cap			
4" PVC	locking cap			

Perforations: factory sawed slot  
 Type perforation \_\_\_\_\_  
 Size perforation .020 x 1 1/2 x 6 rows  
 From 22 feet to 32.4 feet  
 From \_\_\_\_\_ feet to \_\_\_\_\_ feet

Surface Seal:  Yes  No Seal Type:  
 Depth of Seal 2' Bentonite 16'  Neat Cement  
 Cement Grout  
 Placement Method:  Pumped  Concrete Grout  
 Poured  
 Gravel Packed:  Yes  No  
 From 20 feet to 34 feet

Date started 12/6/91, 19\_\_\_\_\_  
 Date completed 12/6/91, 19\_\_\_\_\_

7. WELL TEST DATA

TEST METHOD:	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
<u>NO TEST</u>			

9. WATER LEVEL  
 Static water level 24.72 feet below land surface  
 Artesian flow not known G.P.M. \_\_\_\_\_ P.S.I. \_\_\_\_\_  
 Water temperature n/k °F Quality n/k

10. DRILLER'S CERTIFICATION  
 This well was drilled under my supervision and the report is true to the best of my knowledge.  
 Name Wayne Drilling, Inc., Contractor  
 Address P.O. Box 12370 Contractor  
Reno, NV 89510  
 Nevada contractor's license number issued by the State Contractor's Board 22549  
 Nevada driller's license number issued by the Division of Water Resources, the on-site driller 908  
 Signed Wayne Drilling, Inc.  
 By driller performing actual drilling on site or contractor  
 Date September 15, 1992