

PRINT OR TYPE ONLY
 DO NOT WRITE ON BACK

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 18839

1. OWNER SEA Consulting Eng. Inc. ADDRESS AT WELL LOCATION DownTown Reno
 MAILING ADDRESS 950 Industrial Way Plaza & Center, Commercial & Lake
Sparks, NV 89431-6092 Reno, NV
 2. LOCATION SE 1/4 NE 1/4 Sec 11 T. 19 N/S R. 19 E Washoe County
 PERMIT NO. M/O 483 SW well Downtown Reno
Issued by Water Resources Parcel No. Subdivision Name

3. WORK PERFORMED
 New Well Replace Recondition
 Deepen Abandon Other.....
 4. PROPOSED USE
 Domestic Irrigation Test
 Municipal/Industrial Monitor Stock
 5. WELL TYPE
 Cable Rotary RVC
 Air Other Tubex 190

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
Asphalt Concrete		0	5"	5"
Base		5"	8"	3"
Interbedded moist stiff gray clay and moist loose brown sand, coarse grained		8"	2'	1'4"
Moist, Compact, brown cobbly gravelly clayey sand with estimated 35% sand, 15% gravel to 3" diam, est. 30% volume cobble to 12+"		2	5	3
Brown Cobbly slightly clayey gravelly sand w/est. 10% low plastic fines, 70% sand 20%gr.		5	25	20
Brown cobbly gravelly clayey sand w/est 15-20% low plastic fines 60% sand, 20-25% gravel		25	30	5
Brown cobbly gravelly sand w/est. 5% low pl. fines, 70% sand 25% gravel		30	33	3
Brown cobbly gr. clayey sand as from 25-30'		33	34.2	1.2

8. WELL CONSTRUCTION
 Depth Drilled 34.2 Feet Depth Cased 33.5 Feet
 HOLE DIAMETER (BIT SIZE)
 From 9 5/16 Inches 0 Feet 34.2 Feet
 To _____ Inches _____ Feet _____ Feet
 _____ Inches _____ Feet _____ Feet
 CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
4" PVC		SCH 40	0	33
4" PVC end cap				
4" PVC locking cap				

Perforations:
 Type perforation factory sawed slot
 Size perforation .020 x 1 1/2 x 6 rows
 From 23 feet to 33 feet
 From _____ feet to _____ feet

Surface Seal: Yes No Seal Type:
 Depth of Seal bentonite 2' 16' Neat Cement
 Cement Grout
 Concrete Grout
 Placement Method: Pumped Poured

Gravel Packed: Yes No
 From 20 feet to 34.2 feet

9. WATER LEVEL
 Static water level 25.79' feet below land surface
 Artesian flow not known G.P.M. _____ P.S.I. _____
 Water temperature n/k °F Quality n/k

Date started 12/5/91 19_____
 Date completed 12/5/91 19_____

7. WELL TEST DATA

TEST METHOD:	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
<input type="checkbox"/> Bailer <input type="checkbox"/> Pump <input type="checkbox"/> Air Lift			
<u>NO TEST</u>			

10. DRILLER'S CERTIFICATION
 This well was drilled under my supervision and the report is true to the best of my knowledge.
 Name Wayne Drilling, Inc.
P.O. Box 12370
 Address _____
Reno, NV 89510
 Nevada contractor's license number issued by the State Contractor's Board 22549
 Nevada driller's license number issued by the Division of Water Resources, the on-site driller 908
 Signed [Signature]
 by driller performing actual drilling on site or contractor
 Date July 15, 1992