WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 39851
Permit No.
Basin 92B

NOTICE OF INTENT NO. 21411

1. OWNER Roy & Judith Baughman
MAILING ADDRESS 9421 Wigwam Way
Reno, NV 89506

ADDRESS AT WELL LOCATION Same

2. LOCATION NE ¼ SE ¼ Sec. 11 T 20N N/S R 19 E Washoe County
PERMIT NO. (Issued by Water Resources) 088-10-33 (Parcel No.) Golden Valley (Subdivision Name)

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☒ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☒ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Top soil		0	3	3
Brown clay w/DG mixed		3	59	56
Brown rusty weathered granite		59	145	86
Weathered harder granite		145	189	44
Fracture granite (app 2 GPM)	X	189	193	4
Weathered granite		193	231	38
Soft zone (NO WATER)		231	233	2
Weathered granite		233	312	79
Soft zone (app 3 GPM)	X	312	323	11
Weathered granite		323	354	31
Soft zone (app 5 GPM)	X	354	369	15
Weathered granite		369	375	6

92 NOV -3 AM 9:32
STATE ENGINEER'S OFFICE

Date started 10-20-92, 19
Date completed 10-21-92, 19

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 375 Feet Depth Cased 375 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
10	Inches	0	Feet	50	Feet
8 5/8	Inches	50	Feet	375	Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8		.188	0	375

Perforations:
Type perforation factory sawed slot
Size perforation 3/32 x 3 x 5 around
From 170 feet to 190 feet
From 290 feet to 310 feet
From 350 feet to 370 feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 50
Placement Method: ☐ Pumped ☒ Poured
Seal Type: ☐ Neat Cement ☒ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 50 feet to 375 feet

9. WATER LEVEL
Static water level 117 feet below land surface
Artesian flow 10 G.P.M. P.S.I.
Water temperature cold °F Quality clear

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Wayne Drilling, Inc. (Contractor)
Address P.O. Box 12370 (Contractor)
Reno, NV 89510

Nevada contractor's license number issued by the State Contractor's Board 22549
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 923

Signed [signature] (By driller performing actual drilling on site or contractor)
Date October 29, 1992

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (01-67)