NA-29

WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 34876
Permit No.
Basin 61

NOTICE OF INTENT NO. 18290

1. OWNER DEAN RAOHDES
MAILING ADDRESS ELKO, NV

ADDRESS AT WELL LOCATION NORTH OF BARRICK GOLDSTRIKE MINE

2. LOCATION SE ¼ NW ¼ Sec. 11 T. 35 N/~~S~~ X R. 48 E. EUREKA County
PERMIT NO. ~~57790~~ 59063 (Issued by Water Resources) N/A (Parcel No.) N/A (Subdivision Name)

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☒ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☒ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
CLAY, SAND & COBBLE		0	42	42
RHYOLITE (BROWN)		42	540	498
RHYLOTTE (GRAY)		540	913	373
FRAC.RHYOLITE (BROWN)		913	945	32
VOLCANICS (GRAY)		945	1083	138
HARD VOLCANICS (BLACK)		1083	1118	35
FRAC.RHYOLITE (BROWN)		1118	1225	107

Date started OCTOBER 6, 19 92
Date completed NOVEMBER 9, 19 92

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 1225 Feet Depth Cased 1225 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
20 Inches		0 Feet	50 Feet
12-3/4 Inches		50 Feet	1115 Feet
5-7/8 Inches		1115 Feet	1225 Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
14	55	.375	0	50
6-5/8	19	.280	+2	1100
4	11	SCH 40	1100	1225

Perforations:
Type perforation SLOT
Size perforation .125
From 960 feet to 1100 feet
From 1100 feet to 1225 feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 50
Placement Method: ☒ Pumped ☐ Poured
Seal Type: ☒ Neat Cement ☐ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 50 feet to 1100 feet

9. WATER LEVEL
Static water level 923 feet below land surface
Artesian flow N/A G.P.M. N/A P.S.I.
Water temperature 64 °F Quality GOOD

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name LANG EXPLORATORY DRILLING (Contractor)
Address 2286 WEST 1500 SOUTH (Contractor)
SALT LAKE CITY, UT 84104

Nevada contractor's license number issued by the State Contractor's Board 0021976

Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1388

Signed [signature] (By driller performing actual drilling on site or contractor)
Date DECEMBER 9, 1992

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627