WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 39880
Permit No.
Basin 61

NOTICE OF INTENT NO. 22005

1. OWNER Barrick Goldstrike Mine
MAILING ADDRESS Box 29 Elko NV
ADDRESS AT WELL LOCATION GWOP - NBS

2. LOCATION SW ¼ NW ¼ Sec. 18 T. 36 N/S R. 50 E. Eureka County
PERMIT NO. MO-596 (Issued by Water Resources) | Parcel No. | Subdivision Name

3. WORK PERFORMED
[X] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Abandon [ ] Other

4. PROPOSED USE
[ ] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [X] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [X] Rotary [ ] RVC
[X] Air [ ] Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Top Soil		0	5	5'
Sandy Clay		5'	80'	75'
Sand + Gravel		80'	136'	56'
With Clay layers				

Date started 11-21-92
Date completed 11-23-92

7. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [X] Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 136' Feet Depth Cased 136' Feet

HOLE DIAMETER (BIT SIZE)

	From	To
8 3/4 Inches	0 Feet	136' Feet
Inches	Feet	Feet
Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
4"		PVC Sch 80	0	136'

Perforations:
Type perforation Slot Plastic
Size perforation
From 116' feet to 136 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: [X] Yes [ ] No
Depth of Seal 50'
Placement Method: [X] Pumped [ ] Poured
Seal Type: [X] Neat Cement [ ] Cement Grout [ ] Concrete Grout

Gravel Packed: [X] Yes [ ] No 61' Bentonite on Top of Gravel
From 111' feet to 136' feet

9. WATER LEVEL
Static water level 86' feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name AAA Drilling (Contractor)
Address 181-14 Bullion Rd (Contractor)
Elko NV
Nevada contractor's license number issued by the State Contractor's Board
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1283
Signed [signature] (By driller performing actual drilling on site or contractor)
Date 11-25-92

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627

WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 39882
Permit No.
Basin 61

NOTICE OF INTENT NO. 22004

1. OWNER Barrick Goldstrike Mines
MAILING ADDRESS Box 29 Elko NV
ADDRESS AT WELL LOCATION GWOP - NB4

2. LOCATION SE ¼ SE ¼ Sec. 18 T. 36 (N) S R. 50 E. Eureka County
PERMIT NO. MO - 596 (Issued by Water Resources) | Parcel No. | Subdivision Name

3. WORK PERFORMED
[X] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Abandon [ ] Other

4. PROPOSED USE
[ ] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [X] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [X] Rotary [ ] RVC
[X] Air [ ] Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Top Soil		0'	5'	5'
Clay + Small Rock		5'	40'	35'
yellow Clay		40'	80'	40'
Fractored Rock with		80'	123'	43'
Sand + gravel layers				

Date started 11 - 17, 1992
Date completed 11 - 19, 1992

7. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [✓] Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 123 Feet Depth Cased 123 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
8 3/4 Inches	Feet	0 Feet	123 Feet
Inches	Feet	Feet	Feet
Inches	Feet	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
4"		PVC sch 80	0	123

Perforations:
Type perforation Slot Plastic
Size perforation
From 103 feet to 123 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: [X] Yes [ ] No
Depth of Seal 50'
Placement Method: [✓] Pumped [ ] Poured
Seal Type: [X] Neat Cement [ ] Cement Grout [ ] Concrete Grout
Gravel Packed: [✓] Yes [ ] No 48' Bentonite on top of Gravel
From 118 feet to 123 feet

9. WATER LEVEL
Static water level 59' feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name AAA Drilling (Contractor)
Address 181 - 14 Bullion Rd (Contractor)
Elko NV
Nevada contractor's license number issued by the State Contractor's Board
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1783
Signed [signature] (By driller performing actual drilling on site or contractor)
Date 11 - 22 - 92

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627