

PRINT OR TYPE ONLY  
 DO NOT WRITE ON BACK

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 19981

1. Consultant: Simon Hydro-Search Client: Washoe Keystone Fuel  
 OWNER MAILING ADDRESS: 5250 S. Virginia Suite # 280 ADDRESS AT WELL LOCATION: Fourth Street  
Reno, NV. 89502 Reno, NV.  
 2. LOCATION: NE 1/4 SE 1/4 Sec. 10 T. 19 N. N/S R. 19 E Washoe County  
 PERMIT NO. M/O 288A MW-8 Issued by Water Resources Parcel No. Subdivision Name

3. WORK PERFORMED  
 New Well  Replace  Recondition  
 Deepen  Abandon  Other  
 4. PROPOSED USE  
 Domestic  Irrigation  Test  
 Municipal/Industrial  Monitor  Stock  
 5. WELL TYPE  
 Cable  Rotary  RVC  
 Air  Other Tubex

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
Fill, silt, sand, gravel		0	14	14'
cobbles, clay 30-90%				
plastic soft silty clay				
med to coarse grnd sand				
subangular to subrng gravel				
20-30% soft plastic clay		14	18	4'
as above, w/ coarse grnd				
sand, 5% fn grnd well				
sorted minor gravel				
Fn to coarse grnd sand		18	34	16'
no clay 10% fines, 10%				
coarse, fairly well sorted				
inc gravels 20-30% subang				
to subrnded @ 27'				
Cobbles @ 28'				
1st Water @ 29'				
As Above w/ 10-20% clay		34	36	2'
no cobbles,				
Same as 18-34' w/no clay		36	39	3'

8. WELL CONSTRUCTION  
 Depth Drilled 39 Feet Depth Cascd 39 Feet  
 HOLE DIAMETER (BIT SIZE)  
 From 7 1/4 Inches To 0 Feet 39 Feet  
 \_\_\_\_\_ Inches \_\_\_\_\_ Feet \_\_\_\_\_ Feet  
 \_\_\_\_\_ Inches \_\_\_\_\_ Feet \_\_\_\_\_ Feet  
 CASING SCHEDULE  

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2"		Sch 40 PVC	0	14

 Perforations:  
 Type perforation Factory sawed slot  
 Size perforation 020  
 From 14 feet to 39 feet  
 From \_\_\_\_\_ feet to \_\_\_\_\_ feet  
 Surface Seal:  Yes  No Seal Type:  
 Depth of Seal 1ft. Bentonite  Neat Cement  
 Placement Method:  Pumped  Cement Grout  
 Poured  Concrete Grout  
 Gravel Packed:  Yes  No  
 From 25 feet to 39 feet

9. WATER LEVEL  
 Static water level Not Known feet below land surface  
 Artesian flow Not Known G.P.M. P.S.I.  
 Water temperature 66 °F Quality PH 6.8 \*EC=630 uhmos/

10. DRILLER'S CERTIFICATION km  
 This well was drilled under my supervision and the report is true to the best of my knowledge.  
 Name Wayne Drilling Inc.  
 Address P.O. Box 12370  
Reno, NV. 89510  
 Nevada contractor's license number 22549  
 issued by the State Contractor's Board  
 Nevada driller's license number issued by the 908  
 Division of Water Resources, the on-site driller  
 Signed Jerry A. Feldman  
 By driller performing actual drilling on site or contractor  
 Date December 15, 1992

Date started May 20, 1992, 19\_\_\_\_  
 Date completed May 20, 1992, 19\_\_\_\_

7. WELL TEST DATA

TEST METHOD:  Bailer  Pump  Air Lift

	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
NO TEST			

92 DEC 24 AM 10:11  
 STATE ENGINEERS  
 CONTRACTORS