WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 40103
Permit No.
Basin 57

NOTICE OF INTENT NO. 19113

1. OWNER Duck Valley Shoshone Piute Tribe
MAILING ADDRESS P.O.Box 219
Owyhee Nevada 89832

ADDRESS AT WELL LOCATION App. 100' from County Rd./500'W of cemetary
Owhyee Nevada 89832

2. LOCATION SW ¼ SE ¼ Sec. 15 T 47 N/S R 52 E Elko County

PERMIT NO. N/A (Issued by Water Resources) | N/A (Parcel No.) | N/A (Subdivision Name)

3. WORK PERFORMED
[X] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Abandon [ ] Other

4. PROPOSED USE
[ ] Domestic [ ] Irrigation [X] Test
[ ] Municipal/Industrial [ ] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [X] Rotary [ ] RVC
[ ] Air [ ] Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Topsoil		0	5	5
Pea Gravel / Sand		5	15	10
Course Gravel		15	30	15
Sandy Clay		30	55	25
Course Sand		55	60	5
Clay and Sand		60	85	25
Sand 10% / pea Gravel small Cobbles		85	120	35
Clay		120	125	5
Clay /Sand/cobbles & Gravel	X	125	210	85
Boulders / Sand		210	215	5
Gravel and Clay	X	215	230	15
Clay / pea Gravel		230	245	15
Clay / some Boulders		245	273	28
Brown Sandstone fractured		273	280	7
Basalt		280	310	30

RECEIVED
JAN - 7 1993
STATE ENGINEER'S OFFICE

Date started 12-7, 19 92
Date completed 12-11, 19 92

7. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [X] Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
30	5 hrs.	air on rig

8. WELL CONSTRUCTION
Depth Drilled 305 Feet Depth Cased 300 Feet

HOLE DIAMETER (BIT SIZE)

	From	To
9 7/8 Inches	0 Feet	305 Feet
Inches	Feet	Feet
Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6	PVC	Sched. 80	5	165
"	"	"	206	280
"	"	"	300	305
"	Steel	.188	+2	5

Perforations: Type perforation pvc screen
Size perforation .020
From 165 feet to 205 feet
From 280 feet to 300 feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: [X] Yes [ ] No
Depth of Seal 15
Placement Method: [X] Pumped [ ] Poured
Seal Type: [ ] Neat Cement [X] Cement Grout [ ] Concrete Grout

Gravel Packed: [X] Yes [ ] No Silica Sand
From 15 feet to 305 feet

9. WATER LEVEL
Static water level 18' feet below land surface
Artesian flow - G.P.M. - P.S.I.
Water temperature cold °F Quality good

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Humboldt Drilling and Pump Co. (Contractor)
Address P.O.Box 590 (Contractor)
Winnemucca Nevada 89446-0590

Nevada contractor's license number issued by the State Contractor's Board 015234
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1713

Signed By Weber (by driller performing actual drilling on site or contractor)
Date 12-21-92

(Rev. 3-91)

USE ADDITIONAL SHEETS IF NECESSARY

(O)-627