WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 40211
Permit No.
Basin 212

NOTICE OF INTENT NO. 10622

1. OWNER R.C. White Transportation
MAILING ADDRESS c/o Converse Consultants 4670 S. Polaris Ave L.V.
ADDRESS AT WELL LOCATION R.C. White 4499 S. Arville St. Las Vegas, NV 89102

2. LOCATION SE ¼ NW ¼ Sec. 19 T. 21 N/S R. 61 E. Clark County

PERMIT NO. Mo. 2201 (Issued by Water Resources) | Parcel No. | Subdivision Name

3. WORK PERFORMED
☑ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☑ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☑ Rotary ☐ RVC
☑ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Asphalt		0	.5	.5
Gravelly sand		.5	3	2.5
Silty sand tr. gravel.		3	5	2.
Gravelly sand		5	6.5	1.5
Caliche		6.5	8.5	2.
Silty sand trace gravel.		8.5	14.	5.5
Caliche		14	17.5	3.5
Silty sand w/gravel		17.5	20.	2.5
Sandy clay tr. gravel.		20	23	3
Clayey gravel		23	26	3
Sandy clay w/gravel		26	29.5	3.5
Caliche		29.5	33	3.5
Sandy clay tr. gravel		33	40	7.

T.D = 40'

RECEIVED
NOV 20 1992
Div. of Water Resources
Branch Office - Las Vegas, NV

Date started 10. 22, 1992
Date completed 10. 22, 1992

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 40 Feet Depth Cased 40 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
8 Inches		0 Feet	40 Feet
Inches		Feet	Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
4	2 lbs	Sch. 40	0	40

Perforations:
Type perforation factory slotted
Size perforation 0.020
From 15 feet to 40 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☑ Yes ☐ No
Depth of Seal 0-13 / 11-13 Bent.
Placement Method: ☐ Pumped ☑ Poured
Seal Type: ☐ Neat Cement ☑ Cement Grout ☐ Concrete Grout

Gravel Packed: ☑ Yes ☐ No
From 13 feet to 40 feet

9. WATER LEVEL
Static water level 24.5 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Don Wilson (Contractor)
Address 4670 S. Polaris Ave. Las Vegas Nevada (Contractor)
Nevada contractor's license number issued by the State Contractor's Board
Nevada driller's license number issued by the Division of Water Resources, the on-site driller M1817
Signed (By driller performing actual drilling on site or contractor)
Date

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627