

OFFICE ONLY
 Log No. 402-36
 Permit No. 1
 Basin DOB TRACY SEGA.

PRINT OR TYPE ONLY
 DO NOT WRITE ON BACK

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 14922

1. Consultant: Consulting Services Associates Inc ADDRESS AT WELL LOCATION
 1. OWNER: 1000 Bible Way, Suite # 16 Mustang Ranch Inc.
 MAILING ADDRESS Reno, NV. 89502

2. LOCATION: NE 1/4 NE 1/4 Sec 15 T 19N N/S R 21 E Storey County
 PERMIT NO. M/O-240 MW# 2 Mustang Ranch
 Issued by Water Resources Parcel No. Subdivision Name

3. WORK PERFORMED
 New Well Replace Recondition
 Decpen Abandon Other

4. PROPOSED USE
 Domestic Irrigation Test
 Municipal/Industrial Monitor Stock

5. WELL TYPE
 Cable Rotary RVC
 Air Other Tubex

6. LITHOLOGIC LOG

| Material | Water Strata | From | To | Thick-ness |
|--|--------------|------|----|------------|
| Silty Brown Sand (dry) | | 0 | 11 | 11 |
| Silty Brown Clay (damp) | | 11 | 15 | 4 |
| Sticky Brown Clay (tight) | | 15 | 24 | 9 |
| Sand & Gravel | | 24 | 27 | 3 |
| Dark Brown Clay, sticky | | 27 | 30 | 3 |
| Brown Brittle Clay w/ varied color streaks | X | 30 | 33 | 3 |
| Clay Sand & Gravel mixed | X | 33 | 37 | 4 |
| Dark Gray Volcanic Rock | | 37 | 42 | 5 |
| Brown Clay w/ hard streaks | | 42 | 45 | 3 |
| Brown Clay sticky | | 45 | 50 | 5 |

'93 FEB 19 AM 11:29
 STATE ENGINEERS OF NV

8. WELL CONSTRUCTION
 Depth Drilled 50 Feet Depth Cased 50 Feet

HOLE DIAMETER (BIT SIZE)
 From 9 5/16 Inches To 0 Feet 50 Feet
Inches.....Feet.....Feet
Inches.....Feet.....Feet

CASING SCHEDULE

| Size O.D. (Inches) | Weight/Ft. (Pounds) | Wall Thickness (Inches) | From (Feet) | To (Feet) |
|--------------------|---------------------|-------------------------|-------------|-----------|
| 2" | | Sch 40 PVC | 0 | 25 |
| Locking Cap | | | | |
| End Cap | | | | |

Perforations:
 Type perforation Factory Sawn Slot
 Size perforation 0.020

From.....feet to.....feet
 From 25.....feet to.....50.....feet
 From.....feet to.....feet
 From.....feet to.....feet

Surface Seal: Yes No Seal Type:
 Depth of Seal 2' Bentonite Neat Cement
 Placement Method: Pumped Cement Grout
 Poured Concrete Grout

Gravel Packed: Yes No #3 Loan Star Sand
 From 25.....feet to.....50.....feet

9. WATER LEVEL
 Static water level 32.02.....feet below land surface
 Artesian flow.....G.P.M.P.S.I.
 Water temperature.....°F Quality.....

Date started May 31, 1990, 19.....
 Date completed June 1, 1990, 19.....

7. WELL TEST DATA

TEST METHOD: Bailer Pump Air Lift

| | G.P.M. | Draw Down (Feet Below Static) | Time (Hours) |
|---------|--------|-------------------------------|--------------|
| NO TEST | | | |
| | | | |
| | | | |
| | | | |

10. DRILLER'S CERTIFICATION
 This well was drilled under my supervision and the report is true to the best of my knowledge.

Name WAYNE DRILLING INC Contractor
 Address P.O. Box 12370 Contractor
Reno, NV. 89510 Contractor

Nevada contractor's license number 22549
 issued by the State Contractor's Board

Nevada driller's license number issued by the Division of Water Resources, the on-site driller 908

Signed Wayne C. Friedman by driller performing actual drilling on site or contractor
 Date February 17, 1993