WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 40313
Permit No.
Basin 105

NOTICE OF INTENT NO.

1. OWNER Tim McCarthy
MAILING ADDRESS P.O. Box 2518 Gard. NV 89410
ADDRESS AT WELL LOCATION 1529 Desert Wild Court Gard. NV

2. LOCATION NE ¼ NE ¼ Sec. 36 T 13 N/S R 21 E Douglas County
PERMIT NO. (Issued by Water Resources) 23-472-20 (Parcel No.) Wildflower Sub (Subdivision Name)

3. WORK PERFORMED
[X] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Abandon [ ] Other

4. PROPOSED USE
[X] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [ ] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [X] Rotary [ ] RVC
[ ] Air [ ] Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
HILLSIDE ALL		0	3	3
SAND, GRVL, COBBLES		3	60	57
BLDRS, COMPACT GRY CLAY				
COBBLES W BRWN CLAY		60	80	20
CEMENTED SAND, GRAVEL		80	~~105~~	~~25~~
W MIX OF VOL, GRNITE			110	30
		~~105~~ 110		
BRWN CLAYEY SAND			120	10
BRWN CLAYEY SAND		120	185	65
GRVL, COBBLES				
BWN CLAYEY SAND		185	255	70
SAME W COBBLES	X	255	260	5
SOME CLAY W S,	X	260	300	40
GRVL, CBLES				
BLDRS, GRVL	X	300	320	20
SNDY GRY CLAY		320	400	80
GRY CLAY		400	480	80
GRVL, W MINOR	X	480	495	15
GRY CLAY				

Date started Dec 18, 1992
Date completed Dec 23, 1992

7. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [X] Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
35+		

8. WELL CONSTRUCTION
Depth Drilled 495 Feet Depth Cased 495 Feet

HOLE DIAMETER (BIT SIZE)

Inches	From (Feet)	To (Feet)
11	0	470

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8		.188	+2	495

Perforations:
Type perforation SAWCUT
Size perforation 3x 3/32
From feet to feet
From 280 feet to 320 feet
From ~~495~~ 470 feet to 490 feet
From feet to feet
From feet to feet

Surface Seal: [X] Yes [ ] No
Depth of Seal 52
Placement Method: [X] Pumped [ ] Poured
Seal Type: [X] Neat Cement [ ] Cement Grout [ ] Concrete Grout

Gravel Packed: [✓] Yes [ ] No
From 50 feet to 495 feet

9. WATER LEVEL
Static water level 148 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature 58 °F Quality ?

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Lawchock Drilling Inc. (Contractor)
Address Rt 3 2668 Fuller Rd (Contractor)
Minden, NV 89423
Nevada contractor's license number issued by the State Contractor's Board 021268
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1790
Signed [signature] (By driller performing actual drilling on site or contractor)
Date 1/22/93

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O) 627