

OFFICE USE ONLY
 Log No. 40618
 Permit No. 58408
 Basin 66

PRINT OR TYPE ONLY
 DO NOT WRITE ON BACK
N30 E42 048A

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 23587

1. OWNER Firstmiss Gold, Inc. ADDRESS AT WELL LOCATION Getchell Mine
 MAILING ADDRESS Post Office Box 220
Golconda, Nevada 89414 28 Miles Northeast of Golconda, Nevada
 2. LOCATION SW NE 1/4 NW 1/4 Sec. -33 04 39 38 N/S R. 42 - E. Humboldt County
 PERMIT NO. 58516T-58408 Issued by Water Resources Parcel No. Subdivision Name

3. WORK PERFORMED
 New Well Replace Recondition
 Deepen Abandon Other.....
 4. PROPOSED USE
 Domestic Irrigation Test
 Municipal/Industrial Monitor Stock
 5. WELL TYPE
 Cable Rotary RVC
 Air Other.....

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Overburden		0	35	35
Consolidated rock & clay		35	41	6
Hard rock & clay		41	52	11
Consolidated rock & clay		52	90	38
Hard consolidated-rock & clay		90	105	15
Clay & rock		105	159	54
Fractured rock		159	163	4
Gray clay & rock		163	218	55
Fractured rock		218	221	3
Gray clay & rock		221	248	27
Fractured rock & clay		248	329	81
Clay		329	349	20
Gray clay & rock		349	355	6
Gray sticky clay		355	385	30
Gray clay & rock		385	400	15
Hard rock		400	413	13
Hard fractured rock		413	423	10
Hard rock		423	426	3
Hard rock & lite fractures		426	449	23
Granite		449	485	36
Hard granite		485	515	30
Granite		515	681	166
Hard granite		681	705	24

8. WELL CONSTRUCTION
 Depth Drilled 705 Feet Depth Cased 700 Feet
 HOLE DIAMETER (BIT SIZE)
 From To
14 3/4 Inches 0 Feet 700 Feet
 _____ Inches _____ Feet _____ Feet
 _____ Inches _____ Feet _____ Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
10 3/4	28.04	.250	+1	700

Perforations:
 Type perforation Mill Slot
 Size perforation 8 x 3
 From +1 feet to 64 feet blank
 From 64 feet to 700 feet perf
 From 700 feet to 705 feet plug
 From _____ feet to _____ feet _____
 From _____ feet to _____ feet _____

Surface Seal: Yes No Seal Type:
 Neat Cement
 Cement Grout
 Concrete Grout
 Depth of Seal 52 feet
 Placement Method: Pumped Poured
 Gravel Packed: Yes No
 From 52 feet to 705 feet

9. WATER LEVEL
 Static water level 55.47 feet below land surface
 Artesian flow _____ G.P.M. _____ P.S.I.
 Water temperature 65 °F Quality Fair

10. DRILLER'S CERTIFICATION
 This well was drilled under my supervision and the report is true to the best of my knowledge.
 Name Sargent Irrigation Company Contractor
 Address 9955 North Virginia Street Contractor
Reno, Nevada 89506
 Nevada contractor's license number issued by the State Contractor's Board 0021246
 Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1593
 Signed Dan Sargent
 By driller performing actual drilling on site or contractor
 Date March 15, 1993

Date started February 23, 1993
 Date completed March 13, 1993

7. WELL TEST DATA

TEST METHOD:	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
<input type="checkbox"/> Bailer <input checked="" type="checkbox"/> Pump <input type="checkbox"/> Air Lift	<u>150</u>	<u>394.35</u>	<u>24</u>