WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

# WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 40620
Permit No.
Basin 87

NOTICE OF INTENT NO. 12482

1. ~~OWNER~~ Consultant: Enviromental Audit, Inc.
MAILING ADDRESS 1000-A Ortega Way
Placienta, CA. 92670

ADDRESS AT WELL LOCATION Southern Pacific Trans. Co.
Site: Tank Farm
Sparks, NV.

2. LOCATION NW ¼ NW ¼ Sec. 9 T 19N N/S R 20 E Washoe County
PERMIT NO. M/O#- 132 MW#2 (Issued by Water Resources) Parcel No. Subdivision Name

3. WORK PERFORMED
[X] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Abandon [ ] Other

4. PROPOSED USE
[ ] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [X] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [X] Rotary [ ] RVC
[ ] Air [X] Other Tubex

6. LITHOLOGIC LOG

| Material | Water Strata | From | To | Thickness |
|---|---|---|---|---|
| Gravelly Sand, brn, fine to very coarse, subangular | | 0 | 5.5 | 5.5 |
| Gravelly Sand, brn, fine to very coarse, angular to subangular | | 5.5 | 9.5 | 4 |
| Gravelly Sand, dk brn, fine to very coarse, subangular | | 9.5 | 29.5 | 20 |
| Water@ 20' | | | | |

'93 MAR 17 P1:06 STATE ENGINEER

Date started March 15, 1989, 19
Date completed March 15, 1989, 19

7. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [ ] Air Lift

| | G.P.M. | Draw Down (Feet Below Static) | Time (Hours) |
|---|---|---|---|
| NO TEST | | | |

8. WELL CONSTRUCTION
Depth Drilled 29.5 Feet Depth Cased 29.1 Feet

HOLE DIAMETER (BIT SIZE)

| | | From | To |
|---|---|---|---|
| 9 5/16 Inches | | 0 Feet | 29.5 Feet |
| Inches | | Feet | Feet |
| Inches | | Feet | Feet |

CASING SCHEDULE

| Size O.D. (Inches) | Weight/Ft. (Pounds) | Wall Thickness (Inches) | From (Feet) | To (Feet) |
|---|---|---|---|---|
| 4" PVC Blank | | SCH 40 | 0 | 9.1 |
| End Cap | | | | |
| Slip Cap | | | | |

Perforations:
Type perforation Factory Sawed Slot
Size perforation 0.020
From 9.1 feet to 29.1 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: [X] Yes [ ] No
Depth of Seal 6'
Placement Method: [ ] Pumped [X] Poured
Bentonite 2'
Gravel Packed: [X] Yes [ ] No #3 Lone Star
From 9.1 feet to 29.5 feet

Seal Type: [ ] Neat Cement [ ] Cement Grout [X] Concrete Grout

9. WATER LEVEL
Static water level 20 feet below land surface
Artesian flow Not Known G.P.M. P.S.I.
Water temperature n/k °F Quality n/k

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name WAYNE DRILLING, INC. (Contractor)
Address P.O. BOX 12370 (Contractor)
RENO, NEVADA 89510
Nevada contractor's license number issued by the State Contractor's Board 22549
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 908
Signed [signature] (By driller performing actual drilling on site or contractor)
Date March 9, 1993

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627