WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 40747
Permit No.
Basin 212

NOTICE OF INTENT NO. 11946

1. OWNER Clark Co. Dept. of Aviation
MAILING ADDRESS P.O. Box 11005 Airport Stn
Las Vegas NV 89111-1005
ADDRESS AT WELL LOCATION NW Corner of Paradise/Sahara
Las Vegas, NV

2. LOCATION SW ¼ SW ¼ Sec. 22 T. 21 N OR 61 E. Clark County
PERMIT NO. MO 2241 (Issued by Water Resources) | Parcel No. | Subdivision Name

3. WORK PERFORMED: ☑ New Well ☐ Replace ☐ Recondition ☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE: ☐ Domestic ☐ Irrigation ☐ Test ☐ Municipal/Industrial ☑ Monitor ☐ Stock

5. WELL TYPE: ☐ Cable ☑ Rotary ☐ RVC ☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Asphalt		0	.5	.5
Fill		.5	2.5	2.
Clayey silt		2.5	8	5.5
Sandy silt w/clay		8	10	2.
Sandy gravel		10	10.5	.5
Caliche		10.5	12	1.5
Sandy gravel		12	13	1
Clayey silt		13	15.5	2.5
Caliche		15.5	18.5	3.
Silty clay		18.5	22.5	4.
Clayey silt		22.5	25.5	3
Caliche		25.5	27	1.5
Clay w/silt		27	35	8.
T.D. = 35'				

RECEIVED
MAR 26 1993
Div. of Water Resources
Branch Office - Las Vegas, NV

Date started 3-8, 1993
Date completed 3-8, 1993

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 35 Feet Depth Cased 35 Feet

HOLE DIAMETER (BIT SIZE)

	From	To
6 Inches	0 Feet	35 Feet
Inches	Feet	Feet
Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2	.71 lbs	Sch. 40	0	35

Perforations:
Type perforation Factory Slotted
Size perforation 0.020
From 5 feet to 35 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☑ Yes ☐ No
Depth of Seal 0-3 / 1-3 Butt.
Placement Method: ☐ Pumped ☑ Poured
Seal Type: ☐ Neat Cement ☐ Cement Grout ☑ Concrete Grout

Gravel Packed: ☑ Yes ☐ No
From 3 feet to 35 feet

9. WATER LEVEL
Static water level 22 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Don Wilson (Contractor)
Address 4670 S. Polaris Ave. (Contractor)
Las Vegas, NV 89103
Nevada contractor's license number issued by the State Contractor's Board
Nevada driller's license number issued by the Division of Water Resources, the on-site driller M1589
Signed (By driller performing actual drilling on site or contractor)
Date

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627