WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 40493
Permit No.
Basin 087

NOTICE OF INTENT NO. 15397

1. ~~OWNER~~ Consultants: SEA, Incorporated
MAILING ADDRESS 950 Industrial Way
Sparks, NV. 89431

Client:
ADDRESS AT WELL LOCATION Truckee River Fountain Walk
Island Ave.
Reno, NV.

2. LOCATION NW ¼ SE ¼ Sec. 11 T 19N N/S R 19 E Washoe County

PERMIT NO. M/O 346 MW#2 (Issued by Water Resources) | Parcel No. | Subdivision Name

3. WORK PERFORMED
[X] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Abandon [ ] Other

4. PROPOSED USE
[ ] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [X] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [X] Rotary [ ] RVC
[X] Air [ ] Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Clayey Gravelly Sand Fill		0	16	16
Gravelly Silty Sand to		16	22	6
Silty SAndy Gravel				
Gravelly Sandy Clay		22	29	7
Silty Gravelly Sand to		29	35	6
Silty Sandy Gravel				

'93 APR 29 A10:44
STATE ENGINEER'S OFFICE

Date started May 8, 1991, 19
Date completed May 8, 1991, 19

7. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [ ] Air Lift

	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
NO TEST			

8. WELL CONSTRUCTION
Depth Drilled 35 Feet Depth Cased 35 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
9 5/16 Inches		0 Feet	35 Feet
Inches		Feet	Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
4" PVC		SCH 40	1	10
End Cap				
Locking Cap				

Perforations:
Type perforation Factory Slot
Size perforation 0.020
From 10 feet to 35 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: [X] Yes [ ] No
Depth of Seal 0-6'
Placement Method: [ ] Pumped [X] Poured
Bentonite SEal @ 6-8'
Gravel Packed: [X] Yes [ ] No
From 8 feet to 35 feet

Seal Type:
[X] Neat Cement
[ ] Cement Grout
[ ] Concrete Grout

9. WATER LEVEL
Static water level 17' feet below land surface
Artesian flow not known G.P.M. P.S.I.
Water temperature n/k °F Quality n/k

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name WAYNE DRILLING, INC. (Contractor)
Address P.O. BOX 12370 (Contractor)
RENO, NV. 89510
Nevada contractor's license number issued by the State Contractor's Board 22549
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 908
Signed [signature] (By driller performing actual drilling on site or contractor)
Date April 20, 1993

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627