WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 42078
Permit No.
Basin 9-107

NOTICE OF INTENT NO.

1. OWNER Gary Vance
MAILING ADDRESS 14520 Wagon Wheel Rd Carson City Nev
ADDRESS AT WELL LOCATION 6 Charles Way Smith Nev 89430

2. LOCATION NW ¼ SE ¼ Sec. 11 T. 11 N/S R. 24 E. Lyon County
PERMIT NO. Issued by Water Resources
10-461-08 Parcel No.
Subdivision Name

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☒ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Fine To Coarse Sand		0	30	30
Gravel & Rock		30	32	2
Coarse Sand - Clay		32	39	7
Clay - Sand & Gravel		39	58	19
Brown Clay		58	105	47
Brown Clay & Sand		105	115	10
Brown Clay		115	140	25
Fine To Coarse Sand		140	145	5
Brown Clay		145	175	30
Brown Clay & Sand		175	230	55
Coarse Sand & Clay		230	240	10
Coarse Sand &				
Small Rock	X	240	260	20
Coarse Sand - Gravel				
Clay		260	270	10
Brown Clay & Coarse				
Sand		270	275	5
Blue - Gray Clay &				
Coarse Sand		275	278	3
Coarse Sand &				
Brown Clay		278	280	2
Coarse Sand &				
Small Gravel	X	280	303	23

Date started Dec 11, 1992
Date completed Dec 20, 1992

7. WELL TEST DATA
TEST METHOD: ☒ Bailer ☐ Pump ☐ Air Lift

	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
Bailer	25	5	1/2

8. WELL CONSTRUCTION
Depth Drilled 303 Feet Depth Cased 304 Feet

HOLE DIAMETER (BIT SIZE)

Inches	From Feet	To Feet
10 5/8	0	303

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8	12.92	.188	+1	303

Perforations:
Type perforation Sawed
Size perforation 7/32 x 3 x 6 Rows
From 240 feet to 260 feet
From 280 feet to 303 feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 100
Placement Method: ☒ Pumped ☐ Poured
Seal Type: ☐ Neat Cement ☒ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 100 feet to 303 feet

9. WATER LEVEL
Static water level 54 feet below land surface
Artesian flow — G.P.M. — P.S.I.
Water temperature Cold °F Quality Good

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Ogden Bros Drilling (Contractor)
Address 162 N. Bybee Lane (Contractor)
Yerington Nev 89447
Nevada contractor's license number issued by the State Contractor's Board 15646
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 634
Signed Kay Ogden (By driller performing actual drilling on site or contractor)
Date 6-28-93

(Rev. 3-91)

USE ADDITIONAL SHEETS IF NECESSARY

(O)-627