

8 17 93

LOG NO. 42607

BASIN 46

N32 E S33 B

ELKO

R.D. Reynolds Drilling Company
P.O. Box 402
Wells, Nevada 89835
(702) 752-3205

14410

August 9, 1993

State of Nevada
Department of Conservation & Natural Resources
Office of the State Engineer
Division of Water Resources
123 W Nye Lane
Carson City, NV 89706-9940

Dear Sir:

This letter is to inform you of the abandonment of a 6" industrial well drilled for Frehner Construction permit HC-115. Location of the well: NW1/4 of SW1/4 Section 30 T 32 n/s R56E.

First, casing was perforated from 60' to 460'. Casing below this level was screen. Next, a bentonite fluid was circulated from 530', entering hole at a viscosity of 121, until discharged fluid from well was at 63 viscosity. Mud weight was 9.26 lb/gal. Hole was kept full as drill pipe was removed to a depth of 59'. Clear water pumped to remove mud from casing. Drill pipe was removed and 3/8" hole plug was added to produce a bentonite plug from 59' up to 56'. At this point a concrete grout was tremied from 56' to surface. This ended plugging procedure. Start 7/27/93 end 8/2/93.

Thank you for your time in this matter.

Sincerely

Anthony G. Logan

Anthony G. Logan
Nevada Drillers License #1794

LT/lt