Log: A) 43099
B) 43100
C) 43268
Permit #'s
Basin #'s 4-G & 10-177

R.D. Reynolds Drilling Company
P.O. Box 402
Wells, Nevada 89835
(702)752-3205

September 3, 1993

Tom Gallagher
Nevada Division of Water Resources
123 W Nye Lane
Carson City, NV 89706

Re: Well Abandonments Rennox 1, 2, and Tobar

Dear Tom:

Three wells were abandoned by Reynolds Drilling for the Union Pacific Railroad, locations, descriptions, and methods of abandonments are listed below.

43099 A Rennox 6" well site (NW1/4 NW1/4 Sec35 T33 R45) Well as found to be 96' deep. Perforated casing to 43' - ran trammi to 92' - pumped bentonite to surface - pulled up to 50' and pumped in hol plug - pulled up 2' and pumped neat cement to surface.

43100 B Rennox 8" well site (NW1/4 NW1/4 Sec35 T33 R45) Well found to be 80' deep. Abandoned in similar fashion as Rennox 6" well.

43268 C Tobar 6" well site (SW1/4 Sec20 T35 R63) The well was perforated from 50' to top of existing perforations. Ran 1 1/4" pipe in well - mixed mud and circulated well full of bentonite - pulled up 1 1/4" pipe to 50' and pumped in hole plug bentonite. Mixed neat cement and pumped that in to the surface.

Sincerely,

R.D. Reynolds
Owner

RD\ll

At filing in perm. book time pls. make copy & mark as such to file in well "C" location.