WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 44062
Permit No.
Basin 4-59

NOTICE OF INTENT NO. 20863

1. OWNER Baker Hughes INTEQ
MAILING ADDRESS P.O. Box 277
Battle Mountain, NV 89820

ADDRESS AT WELL LOCATION RW-2
Milpark Drilling Fluids
Argenta, NV

2. LOCATION SW ¼ SW ¼ Sec. 6 T 32 N/S R 47 E Lander County
PERMIT NO. M/O 498-C (Issued by Water Resources) | Parcel No. | Subdivision Name

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC
☐ Air ☒ Other Auger

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Brown sandy silt		0	4	4
Brown silty clay		4	9	5
Brown sandy silt	x	9	14	5
Brown clay, silt		14	19	5
Brown silty clay		19	25	6
Brown silty clay, stiff		25	32	7
Brown silt with gravel		32	35	3
Gray/brown sand		35	38	3
Brown silt with gravel		38	40	2

Traffic box cover
0 - 2 ft.

Date started 2-22- , 19 94
Date completed 3-2- , 19 94

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 40 Feet Depth Cased 40 Feet

HOLE DIAMETER (BIT SIZE)

	From	To
12" Inches	0 Feet	40 Feet
Inches	Feet	Feet
Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6" PVC		Sch. 40	0	8

Perforations:
Type perforation Slotted 6" PVC
Size perforation Sch. 40 20 slot
From 8 feet to 40 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 8 ft.
Placement Method: ☐ Pumped ☒ Poured
Seal Type: ☒ Neat Cement ☐ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No 10-20 Silica Sand
From 8 feet to 40 feet

9. WATER LEVEL
Static water level 13.7 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Elsing Drilling & Pump Co., Inc. (Contractor)
Address P.O. Box 919 (Contractor)
Twin Falls, ID 83303-0919
Nevada contractor's license number issued by the State Contractor's Board 0017177
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1479
Signed Arnold Elsing (By driller performing actual drilling on site or contractor)
Date March 23, 1994

(Rev. 3 91)

USE ADDITIONAL SHEETS IF NECESSARY

(O)-627