WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

**PRINT OR TYPE ONLY**
**DO NOT WRITE ON BACK**

STATE OF NEVADA
**DIVISION OF WATER RESOURCES**

# WELL DRILLER'S REPORT

**Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340**

OFFICE USE ONLY
Log No. 44067
Permit No.
Basin H-5a

NOTICE OF INTENT NO. 18900

1. OWNER Baker Hughes INTEQ
MAILING ADDRESS P.O. Box 277
Battle Mountain, NV 89820

ADDRESS AT WELL LOCATION VEW-10
Milpark Drilling Fluids
Argenta, NV

2. LOCATION SW ¼ SW ¼ Sec 6 T 32 N/S R 47 E Lander County
PERMIT NO. M/O 498-C (Issued by Water Resources) Parcel No. Subdivision Name

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC
☐ Air ☒ Other Auger

6. LITHOLOGIC LOG

| Material | Water Strata | From | To | Thickness |
|---|---|---|---|---|
| Brown sandy silt | | 0 | 3 | 3 |
| Brown silt | | 3 | 6 | 3 |
| Brown silty clay | x | 6 | 26 | 20 |
| Harder brown silty clay | | 26 | 32 | 6 |
| Gray sand, coarse mixed with clay | | 32 | 34 | 2 |
| Brown silty clay | | 34 | 38 | 4 |
| Gray sand, coarse mixed with clay | | 38 | 40 | 2 |
| Traffic Box Cover 0 - 2 ft. | | | | |

Date started 2-17, 19 94
Date completed 3-4, 19 94

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

| G.P.M. | Draw Down (Feet Below Static) | Time (Hours) |
|---|---|---|
| | | |

8. WELL CONSTRUCTION
Depth Drilled 40 Feet Depth Cased 40 Feet

HOLE DIAMETER (BIT SIZE)

| | | From | To |
|---|---|---|---|
| 12 Inches | | 0 Feet | 40 Feet |
| Inches | | Feet | Feet |
| Inches | | Feet | Feet |

CASING SCHEDULE

| Size O.D. (Inches) | Weight/Ft. (Pounds) | Wall Thickness (Inches) | From (Feet) | To (Feet) |
|---|---|---|---|---|
| 6" PVC | | Sch. 40 | 0 | 8 |
| | | | | |
| | | | | |

Perforations:
Type perforation Slotted 6" PVC
Size perforation Sch. 40 20 slot
From 8 feet to 40 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 8 ft.
Placement Method: ☐ Pumped ☒ Poured
Seal Type: ☒ Neat Cement ☐ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No 10-20 Silica Sand
From 8 feet to 40 feet

9. WATER LEVEL
Static water level 16.3 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Elsing Drilling & Pump Co., Inc. (Contractor)
Address P.O. Box 919 (Contractor)
Twin Falls, ID 83303-0919
Nevada contractor's license number issued by the State Contractor's Board 0017177
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1479
Signed Arnold Elsing (By driller performing actual drilling on site or contractor)
Date March 23, 1994

(Rev. 3-91)

**USE ADDITIONAL SHEETS IF NECESSARY**

(O)-627