WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

# WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 44287
Permit No.
Basin 69

NOTICE OF INTENT NO. 20485

1. OWNER Joe & MaryAnn Shannon
MAILING ADDRESS P.O. Box 95
Paradise Valley, NV 89426

ADDRESS AT WELL LOCATION
1990 W. Bridge St.
Paradise Valley, NV 89426

2. LOCATION SW ¼ SW ¼ Sec. 26 T. 42 N/S R. 39 E. Humboldt County
PERMIT NO. "NA" (Issued by Water Resources) 04-331-25 (Parcel No.) NONE (Subdivision Name)

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☒ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

| Material | Water Strata | From | To | Thickness |
|---|---|---|---|---|
| Boulders w/s Clay Brown | | 0 | 25 | |
| Brown Clay w/s Rock | | 25 | 35 | |
| Rock and Clay | | 35 | 45 | |
| Clay w/s Rock | | 45 | 73 | |
| Clay w/s Sand and rock. | | 73 | 115 | |
| Sandy Clay Brown | | 115 | 135 | |
| Sand and Clay Brown | | 135 | 165 | |
| Sand w/s Rock | | 165 | 180 | |

Date started 4-1-94, 19
Date completed 4-6-94, 19

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☒ Air Lift

| G.P.M. | Draw Down (Feet Below Static) | Time (Hours) |
|---|---|---|
| 15 | | 5 hrs. |

8. WELL CONSTRUCTION
Depth Drilled 180 Feet Depth Cased 180 Feet

HOLE DIAMETER (BIT SIZE)

| | From | To |
|---|---|---|
| 10 Inches | 0 Feet | 180 Feet |
| Inches | Feet | Feet |
| Inches | Feet | Feet |

CASING SCHEDULE

| Size O.D. (Inches) | Weight/Ft. (Pounds) | Wall Thickness (Inches) | From (Feet) | To (Feet) |
|---|---|---|---|---|
| 6" | | .188 | +1 | 180 |
| | | | | |
| | | | | |

Perforations:
Type perforation Factory Slot
Size perforation 18 X 3"
From 140 feet to 180 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 50 Ft.
Placement Method: ☐ Pumped ☒ Poured
Seal Type: ☐ Neat Cement ☐ Cement Grout ☒ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 50 feet to 180 feet

9. WATER LEVEL
Static water level 78 feet below land surface
Artesian flow NA G.P.M. NA P.S.I.
Water temperature Cold °F Quality GOOD

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name DAVE McNinch (Contractor)
Address 8005 McNinch Rd. (Contractor)
Winnemucca, NV 89445
Nevada contractor's license number issued by the State Contractor's Board 5437
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 730
Signed Gerald Lemonts (By driller performing actual drilling on site or contractor)
Date April 26, 1994

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627