WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 44329
Permit No.
Basin 8-103

NOTICE OF INTENT NO. 22926

1. OWNER Neil Botts
MAILING ADDRESS 127 mary wolf lane Dayton Nevada 89403
ADDRESS AT WELL LOCATION 127 mary lane Dayton, Nevada 89403

2. LOCATION SE ¼ SW ¼ Sec. 20 T. 17 N/S R. 22 E. Storey County
PERMIT NO. N/A (Issued by Water Resources) 03-293-09 (Parcel No.) MARK TWAIN (Subdivision Name)

3. WORK PERFORMED
☑ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☑ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☑ Rotary ☐ RVC
☑ Air ☑ Other mud

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Top Soil and Gravels		0	6	6
Gravels And Boulders		6	23	18
Black Shale		23	260	190
Black Broken Shale	✓	263	300	37

Date started 3-2, 19 94
Date completed 3-6-9, 19 94

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
Developed for about 2 hours and produced about 25 Gallons a min		

8. WELL CONSTRUCTION
Depth Drilled 300 Feet Depth Cased 300 Feet

HOLE DIAMETER (BIT SIZE)

	From	To
10 5/8 Inches	0 Feet	60 Feet
8 3/4 Inches	60 Feet	300 Feet
Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8	13.00	3/16	+1	300

Perforations:
Type perforation Factory Cut
Size perforation 3/16 x 2X 5 Rows
From 260 feet to 300 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☑ Yes ☐ No
Depth of Seal 0-60
Placement Method: ☐ Pumped ☑ Poured
Seal Type: ☐ Neat Cement ☑ Cement Grout ☐ Concrete Grout
Gravel Packed: ☑ Yes ☐ No
From 60 feet to 300 feet

9. WATER LEVEL PER TELCON W/LEACH DRILLING
Static water level 200 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature Cold °F Quality Good

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Leach Drilling Inc (Contractor)
Address Po Box 599 Silver Springs NV 89429 (Contractor)
Nevada contractor's license number issued by the State Contractor's Board 0038841
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1897
Signed [signature] (By driller performing actual drilling on site or contractor)
Date 3-16-94

STATE ENGINEER'S OFFICE APR -8 P 1:15 '94

USE ADDITIONAL SHEETS IF NECESSARY

(Rev. 3-91) (O)-627