WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 44425
Permit No.
Basin 087

NOTICE OF INTENT NO. 20130

Consultant:

1. OWNER ERM-West, INC. ADDRESS AT WELL LOCATION Catelius Corp.
MAILING ADDRESS 2001 P Street, Suite 200 1235 Glendale Ave
Sacramento, CA 95814-5213 Sparks, NV

2. LOCATION SW ¼ NE ¼ Sec. 8 T. 19N N/S R. 20 E. Washoe County
PERMIT NO. M/O#392-A (Issued by Water Resources) MW#4 (Parcel No.) Sparks, NV (Subdivision Name)

3. WORK PERFORMED
[X] New Well [X] Deepen [ ] Replace [ ] Abandon [ ] Recondition [ ] Other

4. PROPOSED USE
[ ] Domestic [ ] Municipal/Industrial [ ] Irrigation [X] Monitor [ ] Test [ ] Stock

5. WELL TYPE
[ ] Cable [X] Rotary [ ] RVC [X] Air [ ] Other TUBEX

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Asphalt		0	.3	.3
Gravel, clay with some boulders, rounded, 8 - 12" dia.		.3	2.7	2.4
Clay, dark gray, moist		2.7	10	7.3
Gravel, cobbles to sand		10	25.3	14.7

Date started 9-26-91, 19
Date completed 9-26-91, 19

7. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [ ] Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 25.3 Feet Depth Cased 25 Feet

HOLE DIAMETER (BIT SIZE)

	From	To
9 5/16 Inches	0 Feet	25.3 Feet
Inches	Feet	Feet
Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
4" PVC		sch 40	0	25
4" PVC	end cap			
4" PVC	security cap			

Perforations:
Type perforation factory sawed slot
Size perforation 0.020 x 1½ x 6 rows
From 10 feet to 25 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: [X] Yes [ ] No
Depth of Seal 6 ft.
Placement Method: [ ] Pumped [X] Poured
Bentonite: 2'
Gravel Packed: [X] Yes [ ] No
From 8 feet to 25 feet

Seal Type: [X] Neat Cement [ ] Cement Grout [ ] Concrete Grout

9. WATER LEVEL
Static water level 12.75 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name WAYNE DRILLING, INC. Contractor
Address P.O. BOX 12370 Contractor
RENO, NV 89510
Nevada contractor's license number issued by the State Contractor's Board 22549
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 908
Signed [signature] by driller performing actual drilling on site or contractor
Date April 7, 1994

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O) 627