WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

# WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 44542
Permit No.
Basin 106

NOTICE OF INTENT NO. 24822

1. OWNER Erich Greimeister
MAILING ADDRESS 226 Pepper Gardenville Nev 89410
ADDRESS AT WELL LOCATION 3256 Vista Villa Gardenville Nev 89410

2. LOCATION SW ¼ SW ¼ Sec. 18 T. 10 N/S R. 22 E. Douglas County
PERMIT NO. none (Issued by Water Resources) 37-502-11 (Parcel No.) Holbrook Highlands (Subdivision Name)

3. WORK PERFORMED
☑ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☑ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☑ Cable ☐ Rotary ☐ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

| Material | Water Strata | From | To | Thickness |
|---|---|---|---|---|
| yellow top soil + rock | | 0 | 20 | 20 |
| aluvial rock and dirt | | 20 | 68 | 48 |
| sharp gravel + large rock | yes | 68 | 96 | 28 |
| yellow clay + small rock | | 96 | 185 | 89 |
| large bolders | yes | 185 | 205 | 20 |
| yellow clay + small rock | | 205 | 232 | 27 |
| sharp gravel | making | 232 | 245 | 13 |
| yellow clay + small rock | | 245 | 260 | 15 |

Date started May 23 1994, 19
Date completed June 28 1994, 19

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☑ Pump ☐ Air Lift

| G.P.M. | Draw Down (Feet Below Static) | Time (Hours) |
|---|---|---|
| 10 + | 200 ft | 2 days |

8. WELL CONSTRUCTION
Depth Drilled 260 Feet Depth Cased 250 Feet

HOLE DIAMETER (BIT SIZE)

| | From | To |
|---|---|---|
| 10 Inches | 0 Feet | 60 Feet |
| 6 Inches | 60 Feet | 260 Feet |
| Inches | Feet | Feet |

CASING SCHEDULE

| Size O.D. (Inches) | Weight/Ft. (Pounds) | Wall Thickness (Inches) | From (Feet) | To (Feet) |
|---|---|---|---|---|
| 8 5/8 | | 188 | 0 | 185 |
| 5 | | 188 | 185 | 250 |

Perforations:
Type perforation factory saw slot
Size perforation 3/32
From 70 feet to 250 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☑ Yes ☐ No
Depth of Seal 50 +
Placement Method: ☐ Pumped ☑ Poured
Seal Type: ☐ Neat Cement ☑ Cement Grout ☐ Concrete Grout
Gravel Packed: ☐ Yes ☑ No
From feet to feet

9. WATER LEVEL
Static water level 130 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature Cold °F Quality good

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Edmund Miller (Contractor)
Address P.O. Box 92 Smith Nev. (Contractor)
Nevada contractor's license number issued by the State Contractor's Board 32166
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 718
Signed Edmund Miller (By driller performing actual drilling on site or contractor)
Date July 5, 94

(Rev. 3-91)

USE ADDITIONAL SHEETS IF NECESSARY

(O)-627