P-25 A

WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 44589
Permit No.
Basin 212

NOTICE OF INTENT NO. 12681

1. OWNER United States Air Force
MAILING ADDRESS Nellis Air Force BAse
North Las Vegas, Nev. 89115

ADDRESS AT WELL LOCATION
Las Vegas Blvd - Range Rd.
Near Tank Farm

2. LOCATION NE ¼ NE ¼ Sec. 4 T 20 N/S R 63 E Clark County

PERMIT NO. MO 2326 Issued by Water Resources | Parcel No. | Subdivision Name

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC
☐ Air ☒ Other Auger

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Sandy Silt		0	13	13
Calichified Silt		13	18	5
Sandy Silt		18	23	5
Silty Clay		23	59	36
Caliche-Pink		59	60	1
Silty Clay		60	68	8
Calichified Silt		68	73	5
Silty Clay		73	77	4
Sandy Clay	78'	77	88	11
Gravelly Clay		88	130	42

'94 MAY 16 P2:37
STATE ENGINEER'S OFFICE

RECEIVED
MAY 18 1994
Div. of Water Resources
Branch Office - Las Vegas, NV

Date started 2-4, 1994
Date completed 2-5, 1994

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
	N/A	

8. WELL CONSTRUCTION
Depth Drilled 130 Feet Depth Cased 110.5 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
6" Inches	0 Feet	130 Feet	
Inches	Feet	Feet	
Inches	Feet	Feet	

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
1"		AST 480-90	0	90.5

Perforations:
Type perforation 1" Slotted P.V.C.
Size perforation .020
From 90.5 feet to 110.5 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 87.5
Placement Method: ☒ Pumped ☐ Poured
Seal Type: ☒ Neat Cement ☐ Cement Grout ☐ Concrete Grout
3% Bentonite
Gravel Packed: ☒ Yes ☐ No
From 87.5 feet to 130 feet

9. WATER LEVEL
Static water level 75.50 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Water Development Corp. (Contractor)
Address 1202 Kentucky Avenue (Contractor)
Woodland, Ca. 95776
Nevada contractor's license number issued by the State Contractor's Board 0012852
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1368
Signed J. Mills Smith (By driller performing actual drilling on site or contractor)
Date

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627