BW-18 DEEPENED

WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 44751
Permit No.
Basin 61-061

NOTICE OF INTENT NO. 26416

1. OWNER BARRICK GOLDSTRIKE MINE
MAILING ADDRESS P.O. BOX 29
ELKO NEVADA 89801

ADDRESS AT WELL LOCATION
BARRICK GOLDSTRIKE MINE

2. LOCATION SE ¼ NW ¼ Sec. 24 T. 36 N/S R. 49 E. EUREKA County
PERMIT NO. 55142 (Issued by Water Resources) | N/A (Parcel No.) | N/A (Subdivision Name)

3. WORK PERFORMED
☐ New Well ☐ Replace ☐ Recondition
☒ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☒ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☒ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
BLACK LIMESTONE		1757	1800	43
LAMINATED FRACTURED				
LIMESTONE		1800	1810	10
LIMESTONE		1810	1860	50
LAMINATED FRACTURED				
LIMESTONE		1860	1880	20
LIMESTONE		1880	1900	20
LAMINATED FRACTURED				
LIMESTONE		1900	1920	20
LIMESTONE		1920	2020	100
LAMINATED FRACTURED				
LIMESTONE		2020	2180	160
LIMESTONE		2180	2200	20

'94 JUN 23 AM 11:56 STATE ENGINEER

Date started MARCH 12, 1994
Date completed MARCH 23, 1994

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 2200 Feet Depth Cased 2200 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
48 Inches		0 Feet	60 Feet
31 Inches		60 Feet	1757 Feet
22 Inches		1757 Feet	2200 Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
42	152	.375	0	60
24	94.62	.375	+1	1340
19	LOUVERED		1719	2200

Perforations:
Type perforation LOUVERED
Size perforation .040
From 1340 feet to 2200 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 100
Placement Method: ☒ Pumped ☐ Poured
Seal Type: ☒ Neat Cement ☐ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 100 feet to 1757 feet

9. WATER LEVEL
Static water level 499 feet below land surface
Artesian flow N/A G.P.M. N/A P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name LANG EXPLORATORY DRILLING (Contractor)
Address 2286 WEST 1500 SOUTH (Contractor)
SALT LAKE CITY UT 84104
Nevada contractor's license number issued by the State Contractor's Board 0021976
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1800
Signed Victor Hernandez (By driller performing actual drilling on site or contractor)
Date 06/10/94

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627