WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 45485
Permit No.
Basin 212

NOTICE OF INTENT NO. 13060

1. OWNER CAL NEV PIPELINE INC
MAILING ADDRESS 412 WEST HOSPITALITY STE 202
P.O. BOX 6346, SAN BERNARDINO, CA 92412

ADDRESS AT WELL LOCATION INTERSECTION OF HACIENDA & VALLEY VIEW

2. LOCATION SE ¼ NE ¼ Sec. 30 T. 21 N/S R. 61 E. CLARK County
PERMIT NO. MO-2400 (Issued by Water Resources) CC. ROW (Parcel No.) (Subdivision Name)

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE MW-14
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
ASPHALT/FILL		0	3.5	3.5
SILTY TO CLAYEY GRAVEL		3.5	20.5	17
SILTY SAND		20.5	22.5	2
SILTY TO CLAYEY GRAVEL		22.5	33.5	11
SILTY SAND		33.5	35.5	2
SILTY TO CLAYEY GRAVEL		35.5	42	6.5
SILTY CLAY		42	43	1
SILTY GRAVEL		43	48	5
SILTY SAND		48	49	1
SILTY GRAVEL		49	53	4
SILTY SAND		53	54	1
SILTY GRAVEL		54	55	1
SILTY CLAY		55	57	2
SILTY SAND		57	59	2
SILTY CLAY		59	60	1
CLAYEY GRAVEL		60	67	7
SILTY CLAY		67	75	8

RECEIVED
MAR 7 1994
Div. of Water Resources
Branch Office - Las Vegas, NV

Date started FEBRUARY 25, 1994
Date completed FEBRUARY 25, 1994

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 75 Feet Depth Cased 70 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
8 Inches		0 Feet	75 Feet
Inches		Feet	Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2.375	0.164	0.154	0	70

Perforations:
Type perforation FACTORY SLOT
Size perforation 0.020
From 45 feet to 70 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 0-35'/35-41' BENTON.
Placement Method: ☐ Pumped ☒ Poured
Seal Type: ☐ Neat Cement ☒ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 41 feet to 75 feet

9. WATER LEVEL
Static water level feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name DONALD WILSON
Address 4670 SO. POLARIS AVE (Contractor)
LAS VEGAS NV 89103 (Contractor)
Nevada contractor's license number issued by the State Contractor's Board
Nevada driller's license number issued by the Division of Water Resources, the on-site driller M1589
Signed Donald J. Wilson (By driller performing actual drilling on site or contractor)
Date MARCH 15, 1994

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627