WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 45491
Permit No.
Basin 212

NOTICE OF INTENT NO. 12152

1. OWNER LAS VEGAS VALLEY WATER DISTRICT
MAILING ADDRESS 3700 W. CHARLESTON LAS VEGAS NV 89153
ADDRESS AT WELL LOCATION JOHN MENDOZA ELEMENTARY SCHOOL, 2000 SOUTH SLOAN LANE LAS VEGAS NV

2. LOCATION NW ¼ SW ¼ Sec. 3 T. 21 N/S R. 62 E. CLARK County
PERMIT NO. M0-2383 (Issued by Water Resources) 320-170-0014 (Parcel No.) Subdivision Name

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE MW JM-1
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC
☐ Air ☒ Other AUGER

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
FILL-SILTY SAND W/GRAV		0	1	1
CLAY TR SAND		1	6	5
SANDY LEAN CLAY		6	12	6
SANDY SILT		12	16	4
SANDY CLAY		16	20	4
SILTY SAND		20	21	1
SANDY CLAY		21	24	3
SANDY SILT TO SILTY SAND		24	26	2
CLAY TR GRAVEL		26	28	2
SILTY SAND TR GRAV		28	29.5	1.5
SANDY CLAY		29.5	31	1.5

RECEIVED
FEB 10 1994
Div. of Water Resources
Branch Office - Las Vegas, NV

Date started FEB 1, 1994
Date completed FEB 1, 1994

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 31 Feet Depth Cased 30 Feet

HOLE DIAMETER (BIT SIZE)

Inches	From (Feet)	To (Feet)
8	0	31

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
3.5	1.4	0.216	0	30

Perforations:
Type perforation FACTORY SLOT
Size perforation 0.020
From 15 feet to 30 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 0-11'/11-13' BENTONITE
Placement Method: ☒ Pumped ☐ Poured
Seal Type: ☐ Neat Cement ☒ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 13 feet to 31 feet

9. WATER LEVEL
Static water level feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name THOMAS HIGH
Contractor
Address 4670 SO POLARIS AVE
Contractor
LAS VEGAS NV 89103
Nevada contractor's license number issued by the State Contractor's Board
Nevada driller's license number issued by the Division of Water Resources, the on-site driller M1869
Signed
By driller performing actual drilling on site or contractor
Date FEB 1, 1994

(Rev. 3-91)
USE ADDITIONAL SHEETS IF NECESSARY
(O)-627