

PRINT OR TYPE ONLY  
DO NOT WRITE ON BACK

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 3122

Consultant: OWNER Klohn Leonoff Ltd. ADDRESS AT WELL LOCATION Siskon Corporation  
MAILING ADDRESS 10200 Shellbridge Way 333 S. Carson Meadow Dr. Unit 44  
Richmond, B.C., Canada V6X2W7 Carson City, Nevada 89701  
2. LOCATION SW 1/4 SW 1/4 Sec 6 T 16N N/S R 21 E Storey County  
PERMIT NO. 195 Well KLDH-61 Issued by Water Resources Parcel No. \_\_\_\_\_ American Flat Valley Subdivision Name

3. WORK PERFORMED  New Well  Replace  Recondition  Deepen  Abandon  Other \_\_\_\_\_  
4. PROPOSED USE  Domestic  Irrigation  Test  Municipal/Industrial  Monitor  Stock  
5. WELL TYPE  Cable  Rotary  RVC  Air  Other \_\_\_\_\_

6. LITHOLOGIC LOG

| Material   | Water Strata | From | To  | Thickness |
|--|--------------|------|-----|-----------|
| Silt, little gravel, low plasticity, reddish brown   |              | 0    | 6   | 6         |
| Andesite, greenish grey, light brownish grey, medium brownish grey, silty sandy clay matrix. |              | 6    | 25  | 19        |
| Andesite, greenish grey, reddish brown sandy silt matrix.                                    |              | 25   | 35  | 10        |
| Andesite, grey-black, grey-brown, stiff, silty clay matrix.                                  |              | 35   | 40  | 5         |
| Andesite, grey-black, purple-brown low plasticity silt matrix                                |              | 40   | 65  | 25        |
| Volcanics, reddish brown to dark grey, dark brown low plasticity silt matrix                 |              | 65   | 85  | 20        |
| Andesite, dark grey, dark brown, low to medium plasticity silty matrix.                      |              | 85   | 100 | 15        |

8. WELL CONSTRUCTION  
Depth Drilled 100 Feet Depth Cased 100 Feet  
HOLE DIAMETER (BIT SIZE)  
From \_\_\_\_\_ To \_\_\_\_\_  
6 1/8 Inches \_\_\_\_\_ Feet 100 Feet  
Inches \_\_\_\_\_ Feet \_\_\_\_\_ Feet  
Inches \_\_\_\_\_ Feet \_\_\_\_\_ Feet

CASING SCHEDULE

| Size O.D. (Inches) | Weight/Ft. (Pounds) | Wall Thickness (Inches) | From (Feet) | To (Feet) |
|--------------------|---------------------|-------------------------|-------------|-----------|
| 2" PVC             |                     | sch 40                  | 0           | 100       |

Locking Monuments

Perforations:  
Type perforation Factory Sawn Slot  
Size perforation .020  
From 80 feet to 100 feet  
From \_\_\_\_\_ feet to \_\_\_\_\_ feet  
From \_\_\_\_\_ feet to \_\_\_\_\_ feet  
From \_\_\_\_\_ feet to \_\_\_\_\_ feet

Surface Seal:  Yes  No Seal Type:  Neat Cement  Cement Grout  Concrete Grout  
Depth of Seal 65'  
Placement Method:  Pumped  Poured  
Bentonite Seal 65-70  
Gravel Packed:  Yes  No Lone STAR #3  
From 70 feet to 100 feet

9. WATER LEVEL  
Static water level 99 feet below land surface  
Artesian flow \_\_\_\_\_ G.P.M. n/a P.S.I.  
Water temperature n/a °F Quality n/a

10. DRILLER'S CERTIFICATION  
This well was drilled under my supervision and the report is true to the best of my knowledge.  
Name Wayne Drilling, Inc. Contractor  
Address P.O. Box 12370 Contractor  
Reno, Nevada 89510  
Nevada contractor's license number issued by the State Contractor's Board 22549  
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 908  
Signed [Signature] By driller performing actual drilling on site or contractor  
Date July 11, 1994

Date started September 28, 1989  
Date completed September 28, 1989

7. WELL TEST DATA

| TEST METHOD: <input checked="" type="checkbox"/> Bailer <input type="checkbox"/> Pump <input type="checkbox"/> Air Lift | G.P.M. | Draw Down (Feet Below Static) | Time (Hours) |
|---|--------|-------------------------------|--------------|
| No test   |        |                               |              |