



Log # 49148

# Field Exploratory Boring Log VE-5

OVM PPM	Blows/6"	Sample Number	Well Construction	Depth (ft)	Soil Group (USCS)	Materials Description
			Wellbox 0 - 1 Ft.	0		Asphalt
			Neat Cement	0 - 5		Silt (ML) Brown (10YR 4/3); stiff, moist, 85% silt, 15% fine to coarse sand.
			Bentonite 5-7 Ft.	5 - 7		
			2-in. Sch. 40 PVC - Solid	7 - 10		Gravel (GW) Dark Gray (10 YR 4/1); dense, moist to saturated, 85% fine to coarse gravel, 15% fine to coarse sand, subangular to rounded particles.
			Coarse Aquarium Sand Sandpack	10 - 16.5		Color change to Very Dark Gray (10YR 3/1), 75-80% fine to coarse gravel, 20-25% fine to coarse sand.
			2-in. Sch. 40 PVC - 0.05-in. Mill Slot	16.5 - 18		Groundwater encountered at approximately 16.5-17 feet.
		VE-5 -16.5'		18		Total Depth of Boring = 18.0 ft.

'95 MAY 4 M113  
 STATE ENGINEERS DEPT.

**BORING  
VE-5**

**UNOCAL CORPORATION - CERT**  
 Former Unocal SS No. 6979  
 475 East Prater Way  
 Sparks, Nevada

Borehole Diameter: 6 inches  
 Logged by: C. Galantine  
 Driller: Westex  
 Date Started: 4-12-95  
 Date Completed: 4-12-95

**enviros®**  
 95109.09