

PRINT OR TYPE ONLY
 DO NOT WRITE ON BACK

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

page 1 of 2 pages
 NOTICE OF INTENT NO. 14915

Consultant:

1. OWNER Kennedy/Jenks, Inc. Client: _____
 MAILING ADDRESS 160 Hubbard Way, No. 2 ADDRESS AT WELL LOCATION _____
Reno, Nevada 89502 Refuse, Inc
Lockwood Landfill Lockwood, NV.
 2. LOCATION BABA 1/4 1/4 Sec. 27 T. 19N N/S R. 21 E Storey County _____
 PERMIT NO. M/O 253 LL-1 Parcel No. 04-131-03 Subdivision Name Lagomarsino Canyon
Issued by Water Resources Parcel No. Subdivision Name

3. WORK PERFORMED
 New Well Replace Recondition
 Deepen Abandon Other _____

4. PROPOSED USE
 Domestic Irrigation Test
 Municipal/Industrial Monitor Stock

5. WELL TYPE
 Cable Rotary RVC
 Air Other _____

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
Well Graded Gravel w/clay 70% fractured to subangular gravel (predominantly basalt) 8-15mm, well grade. 20% fine sand 1-.1mm, 10% Plastic fines, dusky yellowish brown.		0	10	10
Silty Sand 60% well graded sand 5-.1mm, 3-% slightly to plastic fines, 10% gravel 6-10mm, angular fragments, dark yellow		10	15	5
Well graded gravel w/ silt & sand: 70% well graded gravel 15-6mm, angulat fragments, 20% well graded sand, angular to subrounded grains, 10%nonplastic fines frequent boulder & cobbles in all of the above intervals.		15	22	7
Basaltic Andesite: Aphanitic, minor silicification, hemattie & Pyrite to 2% more intense silification along veins.		22	35	13
Andesite: aphantic, 3% pyrite occuring principally along fracture planes.				

Date started 7-3-90, 19_____
 Date completed 7-5-90, 19_____

7. WELL TEST DATA

TEST METHOD:	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
<input type="checkbox"/> Bailer <input type="checkbox"/> Pump <input type="checkbox"/> Air Lift			
No Test			

8. WELL CONSTRUCTION

Depth Drilled 65 Feet Depth Cased 65 Feet

HOLE DIAMETER (BIT SIZE)
 From 10 Inches 0 Feet 65 Feet
 To _____ Inches _____ Feet _____ Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6" PVC		SCH 80	0	30
End Cap & Locking Cap				
Mild Steel Guard Casing w/ Locking slip cap				

Perforations:
 Type perforation Factory sawed Slot
 Size perforation .020
 From 30 feet to 60 feet
 From _____ feet to _____ feet
 From _____ feet to _____ feet
 From _____ feet to _____ feet

Surface Seal: Yes No Seal Type:
 Depth of Seal 0-23' Neat Cement
 Placement Method: Pumped Cement Grout
 Poured Concrete Grout
 Bentonite seal: 23-25' Lonestar #3
 Gravel Packed: Yes No
 From 25 feet to 63 feet

9. WATER LEVEL

Static water level 24.18 feet below land surface
 Artesian flow N/A G.P.M. N/A P.S.I.
 Water temperature N/A °F Quality N/A

10. DRILLER'S CERTIFICATION

This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Wayne Drilling Inc. Contractor
 Address P.O. Box 12370 Contractor
Reno, Nevada 89510
 Nevada contractor's license number issued by the State Contractor's Board 22549
 Nevada driller's license number issued by the Division of Water Resources, the on-site driller 908
 Signed [Signature] By driller performing actual drilling on site or contractor
 Date April 6, 1995

