WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 51534
Permit No.
Basin 0572

NOTICE OF INTENT NO. 28336

1. OWNER Pegasus Gold
MAILING ADDRESS P.O. Box 330
Imlay, NV 89418

ADDRESS AT WELL LOCATION
I-80 Exit 138
Imlay, NV 89418

2. LOCATION NE SE ¼ NW ¼ Sec. 03 T. 31 N/S R. 33 E. Pershing County
PERMIT NO. 61643 (Issued by Water Resources) waiver # W-459 (Parcel No.) Well #6 (Subdivision Name)

3. WORK PERFORMED
[X] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Abandon [ ] Other

4. PROPOSED USE
[ ] Domestic [ ] Irrigation [ ] Test
[X] Municipal/Industrial [ ] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [X] Rotary [ ] RVC
[ ] Air [ ] Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
top soil		0	4	4
bolders & clay		4	600	596
solid bedrock		600	630	30
fractured bedrock		630	785	155

Date started April 3, 1996, 19
Date completed April 13, 1996, 19

7. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [X] Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
400		11hr.

8. WELL CONSTRUCTION
Depth Drilled 785 Feet Depth Cased 780 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
21	Inches	0	Feet	55	Feet
15	Inches	55	Feet	785	Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
16		.250	+1	55
103/4		.250	+2	580

Perforations:
Type perforation full-flow louvered.070
Size perforation
From 580 feet to 780 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: [X] Yes [ ] No
Depth of Seal 55
Placement Method: [X] Pumped [ ] Poured
Seal Type: [ ] Neat Cement [X] Cement Grout [ ] Concrete Grout

Gravel Packed: [X] Yes [ ] No
From 0 feet to 780 feet

9. WATER LEVEL
Static water level 130 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature 200+ °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Humboldt Drilling & Pump Co., Inc. (Contractor)
Address 4675 W. Winnemucca Blvd. 109-13 (Contractor)
Winnemucca, NV 89445

Nevada contractor's license number issued by the State Contractor's Board 015234

Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1713

Signed (By driller performing actual drilling on site or contractor)
Date 4-15-96

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627

WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
[redacted]
Basin 072

NOTICE OF INTENT NO. 28336

1. OWNER Pegasus Gold
MAILING ADDRESS P.O. Box 330
Imla[redacted]

ADDRESS AT WELL LOCATION I-80 Exit 138
Imlay, NV 89418

2. LOCA[redacted] Pershing County
PERMIT N[redacted]
Issued by Water Resources | Parcel No. | Subdivision Name

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☒ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
top soil		0	4	4
bolders & clay		4	600	596
solid bedrock		600	630	30
fractured bedrock		630	785	155

Date started April 3, 1996, 19
Date completed April 13, 1996, 19

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☒ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
400		11hr.

8. WELL CONSTRUCTION
Depth Drilled 785 Feet Depth Cased 780 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
21 Inches		0 Feet	55 Feet
15 Inches		55 Feet	785 Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
16		.250	+1	55
103/4		.250	+2	580

Perforations:
Type perforation full-flow louvered .070
Size perforation
From 580 feet to 780 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 55
Placement Method: ☒ Pumped ☐ Poured

Seal Type:
☐ Neat Cement
☒ Cement Grout
☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 0 feet to 780 feet

9. WATER LEVEL
Static water level 130 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature 200+ °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Humboldt Drilling & Pump Co., Inc. (Contractor)
Address 4675 W. Winnemucca Blvd. 109-13 (Contractor)
Winnemucca, NV 89445

Nevada contractor's license number issued by the State Contractor's Board 015234

Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1713

Signed [signature]
By driller performing actual drilling on site or contractor

Date 4-15-96

(Rev. 3-91)

USE ADDITIONAL SHEETS IF NECESSARY

(O)-627