WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

# WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 52044
Permit No.
Basin 084

NOTICE OF INTENT NO. 9065

1. OWNER Dave Wendland
MAILING ADDRESS 2055 Pauite Creek Rd.
Reno, Nevada 89510

ADDRESS AT WELL LOCATION 2055 Pauite Creek
Reno, Nevada 89510

2. LOCATION SW ¼ ne ¼ Sec. 17 T 22 N/S R 22 E Washoe County
PERMIT NO. N/A (Issued by Water Resources) | 77-310-15 (Parcel No.) | Palamino Valley (Subdivision Name)

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☒ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☒ Cable ☐ Rotary ☐ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

| Material | Water Strata | From | To | Thickness |
|---|---|---|---|---|
| Rock | | 80 | 90 | |
| Green Clay | | 90 | 96 | |
| Green Clay & Rock | | 96 | 104 | |
| Clay | | 104 | 115 | |
| Red Voc Rock | | 115 | 120 | |
| Clay | | 120 | 125 | |
| Clay | | 125 | 130 | |
| Rock | | 130 | 140 | |
| Fracture Rock | | 140 | 160 | |

Date started January 25, 19 96
Date completed Febraury 22, 19 96

7. WELL TEST DATA
TEST METHOD: ☒ Bailer ☐ Pump ☐ Air Lift

| | G.P.M. | Draw Down (Feet Below Static) | Time (Hours) |
|---|---|---|---|
| Approx. | 20 | 90' | 30 Minutes |

8. WELL CONSTRUCTION
Depth Drilled 160 Feet Depth Cased 160 Feet

HOLE DIAMETER (BIT SIZE)

| | | From | To |
|---|---|---|---|
| 10" | Inches | 0 Feet | 160 Feet |
| | Inches | Feet | Feet |
| | Inches | Feet | Feet |

CASING SCHEDULE

| Size O.D. (Inches) | Weight/Ft. (Pounds) | Wall Thickness (Inches) | From (Feet) | To (Feet) |
|---|---|---|---|---|
| 6 5/8" | 14 | Blank | 0 | 140 |
| | | | | |
| | | | | |

Perforations:
Type perforation Factory
Size perforation 1/8 x 3"
From 140 feet to 160 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 0-100
Placement Method: ☒ Pumped ☐ Poured

Seal Type:
☐ Neat Cement
☒ Cement Grout
☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 100 feet to 160 feet

9. WATER LEVEL
Static water level Flow feet below land surface
Artesian flow 1 G.P.M. 0 P.S.I.
Water temperature cool °F Quality good

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Miller & Sons Drilling Co. (Contractor)
Address P.O. Box 8056 (Contractor)
Reno, Nevada 89507

Nevada contractor's license number issued by the State Contractor's Board 37915

Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1418

Signed Bruce Milley
By driller performing actual drilling on site or contractor
Date February 22,1996

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627