WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 52046
Permit No.
Basin 106

NOTICE OF INTENT NO. 28034

1. OWNER Robert & Sharon Saloney
MAILING ADDRESS 1857 Borda Way Gardnerville NV 89410
ADDRESS AT WELL LOCATION 1857 Borda Way Gardnerville NV 89410

2. LOCATION NW ¼ SW ¼ Sec. 36 T. 13 N S R. 20 E Douglas County
PERMIT NO. Issued by Water Resources | Parcel No. 27-473-03A | Subdivision Name

3. WORK PERFORMED
☑ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☑ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☑ Rotary ☐ RVC
☐ Air ☐ Other Mud

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
overburden		0	3	3
Small Cobbles w/ Sands		3	65	62
Small Volcanic Gravels w/ Clay Seams		65	185	120
Brown Clay		185	210	25
Hard Volcanic Black Shale w/ Little Water	X	210	280	70
Black Sands w/ Little Water	X	280	320	40
Gray Gumbo Clay		320	430	110
Coarse Sands w/ Water	XXX	430	450	20
Coarse Gravels	XXX	450	460	10

Date started 12-26, 1995
Date completed 12-28, 1995

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☑ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
20	85	4 HRS

8. WELL CONSTRUCTION
Depth Drilled 460 Feet Depth Cased 460 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
11 1/4	Inches	0 Feet	55 Feet
9 7/8	Inches	55 Feet	460 Feet
	Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8	13.03	.188	0	460

Perforations:
Type perforation Mill Slot
Size perforation 3x3/32
From 280 feet to 320 feet
From 420 feet to 460 feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☑ Yes ☐ No
Depth of Seal 55
Placement Method: ☐ Pumped ☑ Poured
Seal Type: ☑ Neat Cement ☐ Cement Grout ☐ Concrete Grout
Gravel Packed: ☑ Yes ☐ No
From 55 feet to 460 feet

9. WATER LEVEL
Static water level 210 feet below land surface
Artesian flow G.P.M. 20 P.S.I.
Water temperature 74 °F Quality Good

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name A & H Pump Company (Contractor)
Address 5551 Hwy 50 E #3 Carson City NV 89701 (Contractor)
Nevada contractor's license number issued by the State Contractor's Board 31839
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1905
Signed [signature] (By driller performing actual drilling on site or contractor)
Date 12-28-95

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627