

PRINT OR TYPE ONLY  
 DO NOT WRITE ON BACK

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 24724  
624 STAGE COACH  
GARDNERVILLE

1. OWNER MR + MRS FLYNT ADDRESS AT WELL LOCATION GARDNERVILLE, NV  
 MAILING ADDRESS GARDNERVILLE, NV

2. LOCATION SW 1/4 SW 1/4 Sec. 19 T. 12 N. R. 21 E. DOUGLAS County  
 PERMIT NO. 29-102-06 RUHENSTROTH Subdivision Name

3. WORK PERFORMED  
 New Well  Replace  Recondition  
 Deepen  Abandon  Other \_\_\_\_\_

4. PROPOSED USE  
 Domestic  Irrigation  Test  
 Municipal/Industrial  Monitor  Stock

5. WELL TYPE  
 Cable  Rotary  RVC  
 Air  Other mud

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
<u>SANDY CLAY / COBBLES</u>		<u>0</u>	<u>17</u>	<u>17</u>
<u>SAND GRAVEL</u>		<u>17</u>	<u>58</u>	<u>41</u>
<u>CEMENTED SAND / GRAVEL</u>		<u>58</u>	<u>81</u>	<u>23</u>
<u>SANDY CLAY / GRAVEL</u>		<u>81</u>	<u>162</u>	<u>81</u>
<u>SAND / GRAVEL</u>		<u>162</u>	<u>181</u>	<u>19</u>
<u>CEMENTED GRAVEL / COBBLES</u>		<u>181</u>	<u>202</u>	<u>21</u>
<u>SAND / GRAVEL</u>	<input checked="" type="checkbox"/>	<u>202</u>	<u>207</u>	<u>5</u>
<u>CEMENTED GRAVEL</u>	<input checked="" type="checkbox"/>	<u>207</u>	<u>222</u>	<u>15</u>
<u>SANDY CLAY / GRAVEL</u>	<input checked="" type="checkbox"/>	<u>222</u>	<u>238</u>	<u>16</u>
<u>SAND / GRAVEL</u>	<input checked="" type="checkbox"/>	<u>238</u>	<u>250</u>	<u>12</u>
<u>CEMENTED GRAVEL</u>	<input checked="" type="checkbox"/>	<u>250</u>	<u>320</u>	<u>70</u>

8. WELL CONSTRUCTION

Depth Drilled 320 Feet Depth Cased 320 Feet

HOLE DIAMETER (BIT SIZE)

From	To
<u>10 5/8</u> Inches	<u>0</u> Feet <u>50</u> Feet
<u>9 7/8</u> Inches	<u>50</u> Feet <u>320</u> Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
<u>6 5/8</u>	<u>13</u>	<u>.188</u>	<u>+1</u>	<u>320</u>

Perforations:

Type perforation FACTORY SLOTTED  
 Size perforation 3 x 3/32  
 From 320 feet to 300 feet  
 From 280 feet to 260 feet

Surface Seal:  Yes  No Seal Type:  Neat Cement  
 Cement Grout  
 Concrete Grout

Depth of Seal 50

Placement Method:  Pumped  
 Poured

Gravel Packed:  Yes  No  
 From 50 feet to 320 feet

9. WATER LEVEL

Static water level 22 feet below land surface  
 Artesian flow \_\_\_\_\_ G.P.M. \_\_\_\_\_ P.S.I.  
 Water temperature COLD °F Quality GOOD

Date started 1-2, 1996  
 Date completed 1-10, 1996

7. WELL TEST DATA

TEST METHOD:	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
<input type="checkbox"/> Bailer <input type="checkbox"/> Pump <input checked="" type="checkbox"/> Air Lift	<u>AIR</u>	<u>25+</u>	<u>2</u>

10. DRILLER'S CERTIFICATION

This well was drilled under my supervision and the report is true to the best of my knowledge.

Name EDDCO EXPLORATION, INC Contractor  
 Address 7780 CURRY RD Contractor  
FALLON, NV 89406

Nevada contractor's license number issued by the State Contractor's Board 27673  
 Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1997

Signed [Signature]  
 By driller performing actual drilling on site or contractor

Date 1-11-96