

STATE OF NEVADA  
DIVISION OF WATER RESOURCES  
WELL DRILLER'S REPORT

office use only  
Log No. 52107  
Permit No. \_\_\_\_\_  
Basin 084

NOTICE OF INTENT NO 32118  
5400 Winnemucca Ranch Rd

1. OWNER **Willard Lipscomb** ADDRESS AT WELL LOCATION  
MAILING ADDRESS **5400 Winnemucca Ranch Road**  
**Reno, Nevada** SWNW13

2. Location NE 1/4 SW 1/4 Sec 13 T 22N R 20E  
PERMIT NO. \_\_\_\_\_ PARCEL NO. 076-120-05-202-13

SUBDIVISION NAME Washoe County  
Valley View Units  
132-05

3. WORK PERFORMED | 4. PROPOSED USE | 5. WELL TYPE  
 New Well |  Domestic | Cable  Rotary RVC  
Deepen | Municipal/Industrial | Monitor | Stock | Air | Other  Mud

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Brown, tan, red volcanic sands with brown clay.		0	67	67
Green clay with small green, white sand zone.		67	88	21
Sticky green clay with trace of green white sand.		88	282	282
Green, white, brown red volcanic sand.		282	298	16
Sticky green clay.		298	327	29
Green, white sands with Green clay zones.		327	330	3
Sticky green clay.		330	335	5
Green, white sand with green clay zones.		335	356	21
Green clay sticky.		356	386	30

8. WELL CONSTRUCTION

Depth Drilled **386** feet | Depth Cased **386** feet  
HOLE DIAMETER (BIT SIZE)

	From	To	
10 5/8 inches	0 feet	52 feet	52 feet
8 3/4 inches	52 feet	386 feet	386 feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8	12.92	188	+1.5	386

Perforations::

Type Perforation	factory
Size perforation	3/32
From	356 feet to 336 feet
From	281 feet to 301 feet
From	201 feet to 221 feet
From	feet to feet
From	feet to feet

Surface Seal  YES No  
Depth of Seal **56** feet  
Pumped  Poured  
Gravel Packed:  Yes No  
From **56** feet to **386** feet

Seal Type:  
Neat Cement  
Cement Grout  
 Concrete Grout

9. WATER LEVEL  
Static water level **52** feet below land surface  
Artesian flow **0** GPM **0** P.S.I.  
Water Temperature **cold** Degrees F Quality

Date started **2-2 -96**  
Date completed **2-9 -96**

7. WELL TEST DATA

TEST METHOD:	Bailer	Pump	X	Air Lift
G.P.M.	Draw Down (Feet Below Static)			Time (hours)
<b>20</b>	<b>122</b>			<b>2</b>

10. DRILLER'S CERTIFICATION  
This well was drilled under my supervision and the report is true to the best of my knowledge.  
Name **McKay Drilling, Inc.**  
**2290 Pioneer Drive**  
**Reno, NV 89509**  
NV Contractors No. **14170**  
NV Driller's Lic (on site) **1652**  
Signed \_\_\_\_\_  
By driller performing actual drilling on site or contractor  
Date **3-12-96**