WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

# WELL DRILLER'S REPORT M

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 52305
Permit No.
Basin 212

NOTICE OF INTENT NO. 17539

1. OWNER Calner Pipeline Co.
MAILING ADDRESS P.O. Box 6346 San Bernardino, CA
ADDRESS AT WELL LOCATION SE Corner of Valley View Blvd. and Hacienda

2. LOCATION NW ¼ SW ¼ Sec. 29 T. 21 N/S R. 61 E. Clark County
PERMIT NO. M0-2633 (Issued by Water Resources) 162-29-301-001 (Parcel No.) Subdivision Name

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE RW-27
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC
☐ Air ☒ Other AUGER

6. LITHOLOGIC LOG

| Material | Water Strata | From | To | Thickness |
|---|---|---|---|---|
| SILTY SAND | | 0' | 8' | 8' |
| CALICHE | | 8' | 14' | 6' |
| SAND w/ Clay | | 14' | 20' | 6' |
| SILTY SAND | | 20' | 32 | 12' |
| CALICHE | | 32' | 36' | 4' |
| SILTY SAND w/gravel | | 36' | 45' | 9' |
| CLAYEY GRAVEL | | 45' | 46' | 1' |
| CALICHE | | 46' | 51' | 5' |
| CLAYEY GRAVEL | | 51' | 56' | 5' |
| CLAY | | 56' | 59' | 3' |
| SILTY CLAY | | 59' | 60.5' | 1.5' |
| SILTY CLAY w/ gravel | | 60.5' | 69 | 8.5' |
| CALICHE | | 69' | 72' | 3' |
| CLAY | | 72' | 83' | 11' |

Date started December 27, 1995
Date completed December 27, 1995

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

| G.P.M. | Draw Down (Feet Below Static) | Time (Hours) |
|---|---|---|
| | | |

8. WELL CONSTRUCTION
Depth Drilled 83 Feet Depth Cased 83 Feet

HOLE DIAMETER (BIT SIZE)

| | From | To |
|---|---|---|
| 8 Inches | 0 Feet | 83 Feet |
| Inches | Feet | Feet |
| Inches | Feet | Feet |

CASING SCHEDULE

| Size O.D. (Inches) | Weight/Ft. (Pounds) | Wall Thickness (Inches) | From (Feet) | To (Feet) |
|---|---|---|---|---|
| 4.5 | 1.9 | 0.237 | 0 | 83 |
| | | | | |
| | | | | |

Perforations:
Type perforation Factory Slot
Size perforation 0.020"
From 48 feet to 83 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 0'-25' Concrete Grout, 25'-27' Bentonite
Placement Method: ☐ Pumped ☒ Poured
Seal Type: ☐ Neat Cement ☒ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 27 feet to 83 feet

9. WATER LEVEL
Static water level feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name KENT GROOVER
Address 731 PILOT RD, STE H
LAS VEGAS, NV 89119
Nevada contractor's license number issued by the State Contractor's Board
Nevada driller's license number issued by the Division of Water Resources, the on-site driller M-1953
Signed By driller performing actual drilling on site or contractor
Date

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627