

*J. talo*

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 52374  
 Rec. 19  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_  
*Do not fill in*

Owner Ned Ferraro Driller S.R. Mc Kinney & Son

Address Indian Springs, Nev. Address 1042 So. Main Lic. No. 45

Location of well: Indian Springs, T. 11a N/S, R. 9a E, in Clark County  
or \_\_\_\_\_

Water will be used for Domestic Total depth of well 100 ft.

Size of drilled hole 12" to 50 ft. 10" to 100 ft. Weight of casing per linear foot 10 Gauge

Thickness of casing 10 Gauge Temp. of water \_\_\_\_\_

Diameter and length of casing 8" I.D. to 100ft.  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_

If nonflowing well give depth of standing water from surface 47 ft.

If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.)

Date of commencement of well 11/23/58 Date of completion of well 11/25/58

Type of well rig 72 Speed Star

## LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	35	35	Brown clay & Gravel
35	50	15	Gravel
50	55	5	Brown rock
55	65	10	Brown clay & gravel
65	80	15	Brown clay & gravel (Water)
80	85	5	Brown clay & gravel
85	90	5	Brown clay & gravel (Water)
90	97	7	Brown clay & gravel
97	100	3	Gravel (Water)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 57 to 100 ft.

Other aquifers 85 to 90  
65 to 80

First water at 65 feet.

Casing perforated

from 65 to 100 ft.

Size of perforations

3/16/x 10"



