

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 52445  
 Rec. 19  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_  
 Do not fill in

Owner Guta Schenck Driller J. G. Gibson

Address Indian Springs, Nev. Address Indian Springs Lic. No. 411

Location of well:  $\frac{1}{4}$   $\frac{1}{4}$  Sec. 17,  $\frac{1}{4}$  N/S, R5 E, in Truckee Clark County

Water will be used for Domestic (House) Total depth of well 150

Size of drilled hole 8" Top round 10 3/4" Weight of casing per linear foot \_\_\_\_\_

Thickness of casing 10 gauge Temp. of water normal

Diameter and length of casing 6" 28 ft joints  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_

If nonflowing well give depth of standing water from surface 22 ft.

If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.)

Date of commencement of well Nov. 10-64 Date of completion of well Nov. 17, 1964

Type of well rig Bucyrus Erie Spudder

RECORDED  
 NOV 23 1964  
 LAS VEGAS, NEVADA

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	3	3	Top soil
3	36	33	fill
36	38	2	Gravel (carrying water)
38	80	42	shale & rock
80	86	6	fine gravel (water)
86	150	64	rock

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 80 to 86 ft.

Other aquifers \_\_\_\_\_

First water at 36 feet.

Casing perforated

from 80 to 150 ft.

Size of perforations

3/16

